



Xerox® VersaLink® C625 Color Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to **ConnectKey.com**.

System Specification		
Speed ¹	Color and Black-and-White: Up to 52/50 ppm Letter/A4	
	Duplex Print Speed: 40/38 ipm Letter/A4	
Monthly Duty Cycle ²	Up to 150,000 pages	
Recommended Average Monthly Print Volume	Up to 20,000 pages	
Processor/Memory/ Hard Drive	Quad Core 1.2GHz/4 GB system memory/32 GB eMMC/ Optional: 500+GB HDD	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, NFC; Optional: Wi-Fi®/Wi-Fi Direct® with Xerox® Dual Band WiFi® and Bluetooth® Kit (Bluetooth for iBeacon®)	
Controller Features	Unified Address Book, Remote Control Panel, Configuration Cloning, Fleet Orchestrator, Configuration Watchdog, Security Dashboard, Adaptive Learning	
Copy and Print		
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 dpi	
First-Print-Out Time (as fast as)	6.6 seconds color/5.8 seconds black-and-white	
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	6.3 seconds color/5.7 seconds black-and-white	
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6	
Print Features	Print from USB, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Encrypted Secure Print, Xerox® WorkCentre® Earth Smart Driver Settings Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs, Print Around, Print on Alternate Paper	
Mobile and Cloud Ready		
Universal Print Ready	Microsoft Universal Print is a cloud print service, available to Microsoft 365 subscribers. It removes the need for on-site print servers and leverages the built-in drivers included in the Windows 10 and 11 PCs. You can enjoy the benefits of cloud hosting with a driverless setup for all Windows 10 and 11 clients. Utilize the Print Support App (PSA) by Xerox (Requires installation of Xerox Print and Scan Experience App) to gain access to the Xerox Print Properties user interface.	
Mobile Connectivity	Near Field Communication (NFC); Optional: Wi-Fi® Direct, Wi-Fi® (802.11 b/g/n/ac) AirPrint (iOS) including iBeacon³ (Bluetooth) for AirPrint Discovery	
Mobile Printing	Mopria® Print, Apple® AirPrint®, Xerox® Print Service (Android), Xerox® @PrintByXerox App; Optional: Xerox® Workplace App (iOS/Android), iBeacon³ (Bluetooth) for AirPrint Discovery	
Mobile Scanning	Mopria® Scan, Apple® AirPrint® Scan, Xerox® Easy Assist App; Optional: Xerox® Workplace App (iOS/Android), Scan to Microsoft OneDrive, Google Drive and DropBox	
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® Content Management Platform (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions)	

Xerox® Workflow Central Platform	Optional: One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases (xerox.com/en-us/office/software-solutions/workflow-central)	
Xerox® Workplace Suite and Xerox® Workplace Cloud	tional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their at fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these pabilities in both an on-premises server version (Workplace Suite) and a cloud based-version (Workplace Cloud) of this solution (xerox.com/en-us/office/int-management-solutions)	
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop, or mobile login credentials to log in to your VersaLink MFPs with direct connections to popular cloud identity providers Okta, Ping Identity, and Microsoft® Azure	
Scan		
Standard Features	Destinations: Scan to USB/Email/Network SFTP, SMB, HTTP, HTTPS, FTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: 1-Touch Apps, Optical Character Recognition (OCR), Password-protected PDF, Scan Preview, Scan to Folder, Scan to Home, Scan to Print, Searchable PDF, Single/Multi-Page PDF/TIFF, Touchless Workflow Accelerators, TWAIN Support, Unified Address Book	
Optional Features	Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive), Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at xerox.com/Software-Solutions, Print from and Scan to Xerox® DocuShare® Go Content Management Platform	
Fax		
Standard Features	Fax Build Job, Network Server Fax Enablement, Walk-up Fax includes LAN Fax, Direct Fax, Fax Forward to Email, or SMB Share	
Security		
Standard Features	802.1x, Access Control, AES 256-bit, Audit Log, Automated threat response through Trellix DXL*, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) Integration, Common Criteria Certification, Configuration Watchdog, Encrypted Secure Print, FIPS 140-3, Firmware Verification, HTTPS, Immediate Image Overwrite for optional hard disks4, IPsec, Job Level Encryption via HTTPS and Drivers, Local Authentication (Internal Database), LogRhythm SIEM integration, Microsoft Universal Print/IPP with Print Support Application (Secure Print and Secure Release), Network Authentication, Port/IP/Domain Filtering, Security Certificates utilizing ECDSA, Security Manager, Security Templates, Serverless Card Authentication, SFTP and Encrypted Email, SHA-256 Hash Message Authentication, SIEM integration (Splunk, LogRhythm, Trellix ESM*), Signed Email, SNMPv3, TLS1.1/1.2/1.3, Trellix Embedded Control Allowlisting*, Trellix ePolicy Orchestrator®*, Trusted Boot, Trusted Platform Module (TPM 2.0), User Access, User Permissions	
Optional Features	Trellix Integrity Control*, Xerox® RFID Card Reader, Hard Disk (AES 256-bit) with multi-pass Image Overwrite ⁶ , Xerox® Workplace Cloud/Suite Print Management and Content Security; WPA2™ and WPA3™ with Xerox® Dual Band WiFi® and Bluetooth® Kit (Bluetooth for iBeacon™); Xerox® Workplace Cloud Suite Print Management and Content Security, learn more at xerox.com/WorkplaceSolutions	
Print Management		
Standard Features	Xerox® Standard Accounting Tool (Copy, Print, Scan, Fax, Email), Network Accounting Enablement	
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at xerox.com/PrintManagement	
Optional Artificial Intellige	nce Apps (Available via Xerox App Gallery)	
Optional Features	Xerox® Note Converter App utilizes the power of AI to make sense of handwriting, allowing you to quickly convert your notes into an MS Word document or a digital file. Easily edit, store, and share your notes with everyone in that important meeting you just left, saving you precious time. Xerox® Summarizer App creates a summary of documents for viewing, printing, and emailing. Using artificial intelligence (AI), the Summarizer App condenses dozens or even hundreds of pages by reducing the original scanned document to a percentage of the original or by creating a short and concise interpretation of the source text.	
	Xerox® Auto-Redaction App takes advantage of cutting-edge AI technology in Google's Data Loss Prevention (DLP) software, which allows you to select preset Personally Identifiable Information (PII) or custom words and phrases and then automatically redact it.	

Features and Accessories



Single-Pass Duplex Automatic Document Feeder

(DADF) saves time by simultaneously scanning both sides of two-sided documents with up to 104/98 ipm Letter/A4. High paper capacity drives productivity, especially for tasks that require large batches of scanned or copied documents.



The intuitive, tablet-like, 7-inch tiltable touch screen allows you to personalize your experience to get more done in fewer taps. Gain access to an array of productivity boosting apps through the Xerox App Gallery.

Try it out at xerox.com/SIM7.

The 100-Sheet Bypass Tray handles media sizes from 3×5 in to 8.5×14 in/ 76.2×127 mm to 216×356 mm (Includes 550-sheets standard capacity and additional 100-sheet bypass tray).

The 550-Sheet Tray handles media sizes from 4.1×5.8 in to 8.5×14 in/105 $\times 148$ mm to 216×356 mm (Includes 550-sheets standard capacity and additional 100-sheet bypass tray).

OPTIONAL PAPER FEEDING

550-Sheet Tray

Add up to 4 additional 550-sheet trays for a total paper capacity of 2,850 pages.



OPTIONAL ACCESSORIES

Card Reader Kit

500+GB Hard Disk – Add to busy devices to enhance performance and increase capacity for storage, collation and image processing of large-size jobs, 1-Touch Apps, customer-installable fonts, and enable copy build job.



Convenience Stapler – For simple stapling needs, the Convenience Stapler provides offline stapling of printed output and original documents. Staples up to 20 sheets 20 lb/75 gsm.



Wireless Network Adapter



Printer Stand



Adjustable Stand

XEROX® EASY ASSIST APP

With businesses moving to a more flexible work environment, workers need the right technology in place to keep productive and get back to what really matters. Xerox® Easy Assist App allows you to easily and securely manage your device on the go right from your mobile phone, with real-time monitoring of printer performance and instant access to self-support services - all without the need for any IT support. Learn more at xerox.com/EasyAssist.



Device Specification			
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic, Croatian, Ukrainian		
Accessories			
Optional	Convenience Stapler Wireless Network Adapter 500+GB HDD Scan To Cloud Enablement Kit Trellix Integrity Control Enablement Kit* Unicode Font Kit ⁹		
Electrical Requirements			
North America	Voltage: 110–127 VAC +/-10% Frequency: 50/60Hz +/- 3%, 10A		
Europe	Voltage: 220–240 VAC +/-10% Frequency: 50/60Hz +/- 3%, 5A		
Power Consumption			
Running (Average)	Simplex: 690W Duplex: 612W		
Standby Mode	25W		
Auto Off/Sleep Mode	1.0W (Default time to sleep mode = 1 minute)		
Warm-up (from Off)	122 sec		
Recovery from Sleep	As fast as 2.9 seconds		
Operating Environment			
Required Temperature Range	50 to 90°F/10 to 32.2°C		
Required Relative Humidity	15 to 80% RH		
Sound Power Levels	Operating: 7 B(A) or less Standby: 3 B(A) or less		
Sound Pressure Levels	Operating: 55 db(A) or less Standby: 14 db(A) or less		
Dimensions and Weight	Packaged	Unpackaged	
Base Configuration	Width: 27.6 in/700 mm Depth: 28.9 in/735 mm Height: 33 in/838 mm Weight: 116 lbs/52.5 kg	Width: 18.9 in/479 mm Depth: 20.9 in/533 mm Height: 24.4 in/621 mm Weight: 86 lb/39 kg	
550-Sheet tray	Width: 20.7 in/527 mm Depth: 22 in/558 mm Height: 8.5 in/216 mm Weight: 19.7 lb/8.9 kg	Width: 18.2 in/463 mm Depth: 19 in/483 mm Height: 4.7 in/119 mm Weight: 15 lb/6.8 kg	
Printer Stand	Width: 20.7 in/525 mm Depth: 22.2 in/565 mm Height: 9.2 in/235 mm Weight: 37.7 lb/17.1 kg	Width: 18.2 in/463 mm Depth: 20 in/510 mm Height: 17.3 in/440 mm Weight: 32.7 lb/14.8 kg	
Adjustable Stand	Width: 27.2 in/690mm Depth: 26.3 in/670 mm Height 9.1 in/232 mm Weight: 62.6 lb/28.4 kg	Width: 24.6 in/626 mm Depth: 23.5 in/597 mm Height: 20.5 in/521 mm Weight: 50.9lb/23.1 kg	
System Certifications/Regul	atory Compliance		
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertifications.	tions	

Paper Handling				
Single-Pass Duplex Automat	Single-Pass Duplex Automatic Document Feeder (DADF)			
Capacity ⁵	100 sheets			
Speed (Up to)	Duplex: 104 ipm/98 ipm Letter/A4 (Color and Black-and-White) Simplex: 52 ppm/49 ppm Letter/A4 (Color and Black-and-White)			
Paper Sizes	4.1 x 5.8 in to 8.5 x 14 in/105 x 148 mm to 216 x 356 mm			
Weights	14 to 32 lb bond/52 to 120 gsm			
Bypass Tray (Standard)				
Capacity ⁵	100 sheets			
Sizes	Custom Sizes: 3 x 5 in to 8.5 x 14 in/76.2 x 127 mm to 216 x 356 mm			
Weights	16 to 58 lb bond/60 to 218 gsm			
Media Types	Bond Card Stock Custom Duplex Envelopes Glossy Card Stock¹º Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Plain Preprinted Recycled			
Trays 1 (Standard)				
Capacity ⁵	550 sheets			
Sizes	Tray 1: Custom Sizes: 4.1 x 5.8 in to 8.5 x 14 in/105 x 148 mm to 216 x 356 mm			
Weights	16 to 58 lb bond/60 to 218 gsm			
Media Types	Bond Card Stock Custom Duplex Envelopes Glossy Card Stock ¹⁰ Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Plain Preprinted Recycled			

Paper Handling (continued)			
Optional Paper Feeding	Optional Paper Feeding		
Capacity ⁵	550-Sheet Tray: Add up to 4 additional 550-sheet trays		
Sizes	4.1 x 5.8 in to 8.5 x 14 in/105 x 148 mm to 216 x 356 mm		
Weights	16 to 58 lb bond/60 to 218 gsm		
Media Types	Bond Card Stock Custom Duplex Envelopes Glossy Card Stock ¹⁰ Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted Recycled		
Total Capacity	Total Capacity		
Device Total Capacity ⁵	Base Model: 650 sheets 550-Sheet Tray: Add up to 4 additional 550-sheet trays for a total capacity of 2,850 sheets Paper Output: 300 sheets		

Сору	
First-Copy-Out Time (from platen/warmed up Color/Black-and-White)	As fast as 6.3 sec color letter As fast as 5.7 sec black-and-white letter
Sides (input-output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max)	Up to 600 x 600 dpi
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Program-ahead to allow job to be queued while initial job is processed (Copy, Print, Fax, and Scan)
Copy Features	Annotation and Bates™ stamping (with color capability and font size adjustment) Authentication for Services (i.e., Color Copy) Auto Paper Select Auto Reduction & Enlargement (to fit selected paper size) Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Build Job is supported for all Copy (500+GB HDD is required) and ScanTo/Email/Workflow Scanning/Server Fax/Embedded Fax (500+GB HDD is not required) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Touchless Workflow Accelerators

Print		
Resolution (up to)	1200 x 1200 dpi	
Print Features	Application Defaults Banner Sheet Enable/Disable Booklet Layout Cover Selection Fit to New Paper Size Hold All Jobs Image Options (Resolution (Enhanced, High) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax Layout/Watermark N-up (up to 16 pages per sheet) Paper Selection by Attribute Print From Cloud Repositories (Dropbox, OneDrive, and Google Drive) Sample Set Saved Job (color jobs can be printed as black-and-white) Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default) User Permissions	
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, PCL Color jobs can be printed as black-and-white	
Operating Systems	Windows Server 2016 Windows Server 2019 Windows Server 2022 Windows 10 Windows 11 Mac OS 12.x, 13.x, 14.x Fedora® Core Ubuntu® iOS Android Note: For latest supported versions please visit our Drivers & Downloads page and specify your device at support.xerox.com	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD Microsoft Windows Networking over IP Support for Microsoft Universal Print Bonjour® AirPrint® Mopria® IPv6 Most protocols not in use can be disabled	
Font Capability	PCL: 93 scalable fonts, line printer, and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade, and manage Xerox® Devices and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management	
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy, and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others	
Unified Address Book for Fax, Email and Scan to		
Features	Services supported: Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of all services supported	

Scan	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)
Input Speed (up to)	Duplex: 104 ipm/98 ipm Letter/A4 (Color and Black-and-White) Simplex: 52 ppm/49 ppm Letter/A4 (Color and Black-and-White)
Resolution	200 x 200 dpi up to 600 x 600 dpi
Bit Depth	1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)
Maximum Scan Area	8.5 x 14 in (215.9 x 355.6 mm), Legal
Platen	Up to 8.5 x 14 in (216 x 356 mm) Document Feeder: Up to 8.5 x 14 in (216 x 356 mm)
Scan Template Management	Support 250 scan templates Create Xerox® Embedded Web Server (EWS) scan templates and share via device cloning to other multifunction printers' confirmation sheet options
Network Protocols	SFTP, FTP, SMB, HTTP, HTTPS
File Compression	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for black-and-white and within MRC)) Linearized PDF/PDF/A
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value, and other configurations Customized fields viewed on user interface for variable data input Scan To with Metadata: Embedded in scan files using XMP formats Works with expert systems workflow
Scan Features	Auto Background and Shadow Suppression Bound Originals Compression Quality/File Size Control Edge Erase Mixed Size Originals Scan Build Job Original Type (Photo and Text, Photo, Text, Newspaper/Magazine) Reduction/Enlargement Single Touch Scan buttons (up to 10) Size for Size (for mixed size originals) Touchless Workflow Accelerators TWAIN Support/WIA 2.0 Support
Scan to Email (Standard)	
Scan Features	 Auto send to self Email signatures (6 lines each of 128 character max), email message body (user configurable), email Embedded Web Server confirmation sheet options Email signing (requires Smart Card option) Scan to Email S/MIME Encryption Touchless Workflow Accelerators
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino), Device Address Book
Scan To	
Standard Features	Scan to Email Scan to Home Scan to Mailbox Scan to Network (using Secure FTP/HTTP/HTTPS) Scan to Network Folder (using Secure FTP/HTTP/HTTPS) Scan to Network Folder (using Secure FTP/HTTP/HTTPS) Scan to PC/Server Client (SMB or FTP) Scan to Print Scan to USB Touchless Workflow Accelerators
Optional Features	Native Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive)
Workflow Scanning (Optiona	l features)
Scanning Apps and Xerox App Gallery	Scan to: Dropbox, Google Drive, Microsoft OneDrive, Microsoft Office 365, Box, Xerox® Workplace App (iOS/Android) See the full list of apps available in the Xerox App Gallery: xerox.com/AppGallery

Security

Features

- Audit Log
- Cisco® Identity Services Engine (ISE) compatible • Configuration Watchdog (Monitors and remediates 75 security settings in the following areas):
- 802.1x
- Admin Password Reset
- Audit Log
- Automatic Software Upgrade
- Email Alerts
- FIPS 140
- Hold All Jobs
- Immediate Job Overwrite⁴
- Installation Policies
- PII Login Name
- PostScript Passwords
- Remote Services Enablement
- Remote Start (TWAIN)
- Reprint Saved Jobs
- Scan to Mailbox (Internal storage)
- Scheduled Disk Overwrite⁴
- Secure Passcode Length
- Secure Print Device Policies
- SIEM
- SNMP
- System Timeout
- Trellix Embedded Control*
- USB (Print from USB)
- USB (Scan to USB)
- USB Port Management
- User Data Encryption
- Expanded Authentication
 - Digitally signed PDF (when using Smart Card authentication)
 - Encrypted and authentication to SMTP server for Scan to Email
 - Encrypted/Password Protected PDF (when using Email and Network Scan Templates only)
 - FIPS 140 256 bit Hard Disk Encryption⁴, TLS 1.1/1.2/1.3, IPPS, HTTPS, SFTP, SNMPv3
 - Immediate Image Overwrite/Securely delete jobs using approved algorithms⁴
 - Local Authentication (internal database)
 - Network authentication to access device and/or device services via Kerberos (UNIX/Windows Server 2008), SMB (Windows Server 2008, Windows Server 2012), NDS, LDAP authentication
 - On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk⁴
 - Smart Card authentication 144k CAC/PIV Card Support (2048 bit certificate key)/.NET
 - Secure Data
 - Secure Print (up to 10 digit PIN or Network Authentication)
- Expanded Authorization
 - Authorization per user per service
 - SA access based on network credentials
- User Permissions required to access Print and Print Features (e.g., color access, or time restrictions) reflects in the print driver
- Hide Print Job Names
- IP Filter, IPsec, IPv6, TLS V1.0, V1.2, V1.3, SNMP V1/V2/V3, HTTPs, 802.1X, SFTP
- Port disablement including USB ports
- Secure Print (up to 10 digit PIN or Network Authentication)
- Security Dashboard
- Security Information and Event Management (SIEM) support for Trellix Enterprise Security Manager*, LogRhythm, and Splunk
- Security Templates
- Splunk SIEM integration
- Trellix Embedded Control* (Allowlisting), Trellix Integrity Control* (optional)
- Trusted Platform Module 2.0
- WPA2™ and WPA3™ are supported by the Dual Band Wi-Fi® and Bluetooth® Kit

Fax		
Walk-up Fax Features		
Compatibility	ITU (CCITT) Group 3	
Speed/Modems	Single V.34 modem: V.34 33600 – 2400 BPS. Less than 4 seconds per page transmission time	
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3	
Resolution	Walkup Send: BW Resolution Standard 200 x 100 dpi (Send) 200 x 100 dpi, 204 x 98 dpi (Receive) Fine 200 x 200 dpi (Send) 200 x 200 dpi, 204 x 196 dpi (Receive) SuperFine 300 x 300 dpi (Send) 300 x 300 dpi, 204 x 391 dpi (Receive) UltraFine 600 x 600 dpi (Send) 600 x 600 dpi, 400 x 400 dpi, 408 x 391 dpi (Receive) Color Resolution Fine 200 x 200 dpi (Send) 200 x 200 dpi (Receive) SuperFine 300 x 300 dpi (Send) 300 x 300 dpi, 400 x 400 dpi (Receive) Receive: Accepts all sizes	
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity) Device Address Book (up to 5,000 contacts) Touchless Workflow Accelerators	
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode — Manual (size, margin, stock, header)/Auto Output Tray Selection Up to 200 Password-protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay	
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only	
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite ⁴ Report, Mailbox Report, Broadcast Report	
Directory Access	Utilizes the Unified Address Book Group fax available	
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25 minute intervals	
Auto Resend	Up to 5 attempts	

Device Management		
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, AutoIP (Self Assigned Address)DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS, Bonjour	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System-Power MIB, Fleet Orchestrator, Configuration Watchdog, Security Dashboard, Xerox® Easy Assist App	
Xerox® Easy Assist App	Xerox® Easy Assist App allows you to easily and securely manage your device on the go right from your mobile phone, with real-time monitoring of printoperformance and instant access to self-support services – all without the need for any IT support	
Xerox® CentreWare® Web Software	Web-based server application for network administrators that permits Web browser-based device management from any workstation, nether running on Windows, UNIX, or any other operating system: Works with any SNMP-managed printer from any manufacturer Remote configuration of SNMP v3 Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management Auto-detect Xerox® CentreWare® Web Software server and download configurations files for touchless remote install	
Xerox® Device Manager	Optional: Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices • Usage collection, chargeback, and billing capabilities • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install	
Xerox® Workplace Cloud	Optional: Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server	
Accessibility	Embedded Web Server conforms to Web Content Guidelines (WCAG) Touchscreen tilt and user interface inversion Touchscreen navigation with keyboard Speech output	
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new VersaLink® to automatically set itself up on the network to be automatically configured	
Xerox [®] Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. office.xerox.com/Software-Solutions	
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at office.xerox.com/Software-Solutions	
Xerox® Embedded Web Serve	er — Integrated Device Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel	
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Template	
Browsers	Brave Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari	
Support	Install print/scan drivers and online support available via support.xerox.com	
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic, Croatian, Ukrainian	
Remote Services		
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time	
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manually manage supplies inventory	
Xerox® Workplace Cloud Direct	Embedded device agent technology allows your printer to connect directly with Xerox® Workplace Cloud for a zero network footprint offering a 'true' cloud-only Print Management and Mobile solution.	
Accounting		
Xerox® Standard Accounting	(Standard)	
Tracking	Copy, Print, Fax, Scan and Email usage	
Accounting	Up to 2,495 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)	
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry standard CSV file 	

Accounting (continued)

Accounting Options – Network Accounting (Allows central server to manage all accounting)

- · Enhanced network accounting with up-to-the-minute data on how the system is being used
- · Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and server fax
- Numerous solutions are available through Xerox Alliance Partners. For details, visit xerox.com
- Security enhancements with the addition of HTTPS protocol support
- Device requests account authentication from third-party server enabling larger databases of users and accounts
- Accept Authentication Login at control panel and pass to third-party Networking Account
- Interface with third-party accounting terminal for accounting user interface

Installation Considerations

Clear area around the device is necessary for access and ventilation. The table to the right shows the area needed on each side for correct installation

Top: 11.5 in/292 mm Rear: 4 in/102 mm Left: 6 in/152 mm Right: 20 in/508 mm Front: 20 in/508 mm

What's In The Box

All items contained in the box:

Xerox® VersaLink® C625 Multifunction Printer

AC Power Cord Installation Guide Product Information Flyer Product Safety Sheet Software Update Flyer Software and Documentation CD

CMY Print Cartridges: 7,000 page capacity K Print Cartridge: 8,000 page capacity⁶

Supplies and Accessories		All other regions	
Genuine Xerox Black Standard Capacity Toner Cartridge, Xerox® VersaLink® C625 Color Multifunction Printer (8,000 Pages) ⁶	006R04616	006R04620	
Genuine Xerox Cyan Standard Capacity Toner Cartridge, Xerox® VersaLink® C625 Color Multifunction Printer (6,000 Pages) ⁶	006R04617	006R04621	
Genuine Xerox Magenta Standard Capacity Toner Cartridge, Xerox® VersaLink® C625 Color Multifunction Printer (6,000 Pages) ⁶	006R04618	006R04622	
Genuine Xerox Yellow Standard Capacity Toner Cartridge, Xerox® VersaLink® C625 Color Multifunction Printer (6,000 Pages) ⁶	006R04619	006R04623	
Genuine Xerox Black High Capacity Toner Cartridge, Xerox® VersaLink® C625 Color Multifunction Printer (25,000 Pages) 6	006R04636	006R04644	
Genuine Xerox Cyan High Capacity Toner Cartridge, Xerox® VersaLink® C625 Color Multifunction Printer (16,000 Pages) ⁶	006R04637	006R04645	
Genuine Xerox Magenta High Capacity Toner Cartridge, Xerox® VersaLink® C625 Color Multifunction Printer (16,000 Pages) 6	006R04638	006R04646	
Genuine Xerox Yellow High Capacity Toner Cartridge, Xerox® VersaLink® C625 Color Multifunction Printer (16,000 Pages)6	006R04639	006R04647	
Genuine Xerox Waste Toner Bottle, Xerox® VersaLink® C625 Color Multifunction Printer (170,000 Pages) ⁷	008R13334	008R13334	
Genuine Xerox Black Imaging Kit, Xerox® VersaLink® C625 Color Multifunction Printer (150,000 Pages)8	013R00697	013R00697	
Genuine Xerox 3 Color Imaging Kit, Xerox® VersaLink® C625 Color Multifunction Printer (150,000 Pages)8	013R00698	013R00698	
Staple Cartridge (5,000 Staples)	008R13347	008R13347	
Optional Accessories			
550-Sheet Tray	097N02441		
Convenience Stapler (110v)		097N02442	
Convenience Stapler (220v)		097N02463	
500+GB Hard Disk	097N02443		
Wireless Network Adapter	097N02470		
Printer Stand	097S05244		
Adjustable Stand	497N07994		

- # North America (NA): U.S., Canado
- Europe (XE): U.K., France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland Andorra, Azores, Corsica, Greenland, Iceland, Lichtenstein, Luxembourg, Madeira, San Marino
- *Trellix DXL formerly known as McAfee® DXL, Trellix Embedded Control Whitelisting formerly known as McAfee® Embedded Control Whitelisting, Trellix ePolicy Orchestrator® formerly known as McAfee® ePolicy Orchestrator®, Trellix ESM formerly known as McAfee® ESM, Trellix Integrity Control Enablement Kit formerly known as McAfee® Integrity Control Enablement Kit, Trellix Enterprise Security Manager formerly known as McAfee® Enterprise Security Manager. Trellix brand name will be reflected in future firmware releases.
- ¹ Declared in accordance with ISO/IEC 24734.
- ² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
- Wireless Network Adapter is required for iBeacon.
- 4 Requires 500+GB Hard Disk.
- ⁵ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks
- Average standard pages. Declared in accordance with ISO/IEC 19798. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes, and image quality set-points.
- Waste Toner Container yield will vary depending on type of image, area coverage %, and Job run length.
- Average drum yield is based on a run length of 5 pages of 8.5 x 11 in/A4 LEF pages, with split of 35% color/65% black-and-white pages.
- 9 Not available in all geographies.
- ¹⁰ Weight: 16 to 58 lb bond/88 to 176 gsm.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. Visit xerox.com/About-Xerox/Recycling.

For more information, visit us at xerox.com/Office.

© 2024 Xerox Corporation. All rights reserved. Xerox®, CentreWare®, ConnectKey®, DocuShare®, Global Print Driver®, Green World Alliance®, VersaLink®, and WorkCentre® are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. 09/24 TSK-5675 BR38293 V6CSS-01UB

