

Xerox® VersaLink® C7000 Color Printer



Integrated Office
Finisher type A
(Type GAR not pictured)



Single Tray Module



Single Tray
with Stand



Three Tray Module

The VersaLink® C7000 Color Printer is built on Xerox® ConnectKey® Technology.
For more information, go to www.ConnectKey.com.

| SYSTEM SPECIFICATIONS | VERSALINK® C7000 |
|--|---|
| One-Sided Speed¹ 8.5 x 11 in./A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm | Up to 35 ppm (pages per minute) long edge feed (LEF) Up to 22 ppm Up to 19 ppm |
| Two-Sided Speed¹ 8.5 x 11 in./A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm | 35 ppm (pages per minute) LEF Up to 14 ppm Up to 13 ppm |
| Monthly Duty Cycle² | Up to 153,000 pages/month |
| Recommended Average Monthly Print Volume³ | Up to 10,000 pages |
| Hard Drive | 320 GB HDD (Optional) |
| Processor | 1.05 GHz Dual-Core |
| Memory | 2 GB |
| Connectivity | Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair |
| Controller Features | Configuration Cloning, Xerox Extensible Interface Platform®, Xerox App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support |
| User Interface Languages | English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian |

Xerox® VersaLink® C7000 Color Printer

| DEVICE SPECIFICATIONS | | | | |
|---|--|--------------------|---------------------|--------------------|
| ELECTRICAL REQUIREMENTS | | | | |
| North America | Voltage: 110-127V-10 % /+6 % Frequency: 50/60 Hz +/-3 %, 12A | | | |
| Europe and Other Geographies | Voltage: 220-240V +/-10 % Frequency: 50 Hz +/-3 %, 8A | | | |
| POWER CONSUMPTION | | | | |
| Printing ⁴ | For 110V: 1.6 kWh For 220V: 1.6 kWh | | | |
| Standby Mode ⁴ | 110V: 94 watts or less 220V: 94 watts or less | | | |
| Sleep Mode ⁴ | 110V: 1.0 watts or less 220V: 1.4 watts or less | | | |
| OPERATING ENVIRONMENT | | | | |
| Required Temperature Range (Storage) | 32° to 95° F (0° to 35° C) | | | |
| Required Temperature Range (Operating) | 50 to 90° F (10 to 32° C) | | | |
| Required Relative Humidity | 10% to 85% | | | |
| Sound Power Levels | Printing: 6.75 B(A) or less Standby: 4.10 B(A) or less Full System (including finisher) Printing: 7.52 B(A) Standby: 4.10 B(A) | | | |
| Sound Pressure Levels | Printing: 52.5 dB(A) Standby: 26.0 dB(A) Full System (including finisher) Printing: 60.0 dB(A) Standby: 26.0 dB(A) | | | |
| Boot Time (from Off to UI Ready) | As fast as 98 seconds | | | |
| Warm-up Time (from Sleep to UI Ready) | As fast as 12 seconds | | | |
| DIMENSIONS AND WEIGHT (UNPACKAGED) | WIDTH | DEPTH | HEIGHT | WEIGHT |
| Base Unit | 23.23 in./590 mm | 26.41 in./670.8 mm | 25.08 in./637 mm | 119.71 lb./54.3 kg |
| Base Unit with Single Tray with Stand Module | 24.24 in./615.7 mm | 26.41 in./670.8 mm | 44.04 in./1118.6 mm | 171.08 lb./77.6 kg |
| Base Unit with Three Tray Module | 24.24 in./615.7 mm | 26.41 in./670.8 mm | 44.04 in./1118.6 mm | 178.75 lb./81.8 kg |
| Base Unit with Three Tray Module and Integrated Office Finisher (type A) | 24.24 in./615.7 mm | 26.41 in./670.8 mm | 44.04 in./1118.6 mm | 215.17 lb./97.6 kg |
| Office Finisher (type GAR) | 25.73 in./653.6 mm | 26.41 in./670.8 mm | 38.90 in./988 mm | 195.99 lb./88.9 kg |
| CERTIFICATIONS | | | | |
| To view the latest list of certifications, go to www.xerox.com/OfficeCertifications . | | | | |

Xerox® VersaLink® C7000 Color Printer

| PRINT | |
|----------------------------|---|
| First-Print-Out Time | As fast as 7.6 seconds color |
| | As fast as 5.1 seconds black-and-white |
| Print Resolution | Up to 1200 x 2400 dpi |
| Page Description Languages | Adobe® PostScript® 3™ PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL |
| Maximum Print Area | 4 mm from Lead edge of paper, 2 mm from Side and Trail edges of paper |
| Print Features | Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Color Adjustments (lightness, contrast, saturation, color balance) Color Correction Draft Mode Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default – DN configuration) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings |
| Print from USB | Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A |
| Operating Systems | Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.Support.Xerox.com . |
| Fonts | PostScript fonts: 136 PCL fonts: 83 |

Xerox® VersaLink® C7000 Color Printer

| | |
|--|--|
| Xerox® Global Print Driver® | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. |
| Xerox® Pull Print Driver | Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others. |
| MOBILE SOLUTIONS AND MOBILE DEVICE APPS | |
| Apple® AirPrint® | Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network. |
| Mopria® Certified | ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily. |
| Xerox® @printbyXerox App | @printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel. |
| Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store) | The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store. |
| Xerox® Workplace Suite and Xerox® Workplace Cloud | Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution. |
| SOFTWARE SOLUTIONS | |
| Xerox® ConnectKey® Apps (Found at the Xerox App Gallery) | Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the device. |
| SECURITY | |
| Security Features | <p> Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM) </p> <p>*Requires HDD/Productivity Kit</p> |

ACCOUNTING**XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)**

| | |
|-------------------|--|
| Tracking | Print usage |
| Accounting | Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions) |
| Features | Administrator can manage the feature via the Embedded Web Server. |

ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)

| | |
|--|--|
| | <ul style="list-style-type: none"> Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device print usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account |
|--|--|

PAPER HANDLING**BYPASS TRAY**

| | |
|--|---|
| Capacity⁵ | 100 sheets |
| Sizes | Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in./88.9 x 98.4 mm to 297 x 431.8 mm |
| Weights One-sided: Two-sided: | 16 lb. bond to 80 lb. cover/60 to 216 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm |
| Types | Bond Plain Paper Cardstock Custom Envelopes <div> Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock </div> Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Pre-Printed Recycled |

TRAY 1

| | |
|--|---|
| Capacity⁵ | 520 sheets |
| Sizes | Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm |
| Weights One-sided: Two-sided: | 16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm |
| Types | Bond Plain Paper Cardstock Custom Hole Punched <div> Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock </div> Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled |

SINGLE TRAY MODULE (OPTIONAL)

| | |
|--|---|
| Capacity⁵ | 520 sheets |
| Sizes | Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm |
| Weights One-sided: Two-sided: | 16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm |
| Types | Bond Plain Paper Cardstock Custom Hole Punched <div> Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock </div> Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled |

| | | | |
|--|--|---|---|
| SINGLE TRAY MODULE WITH STAND (OPTIONAL) | | | |
| Capacity ⁵ | 520 sheets | | |
| Sizes | Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm | | |
| Weights One-sided: Two-sided: | 16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm | | |
| Types | Bond Plain Paper Cardstock Custom Hole Punched | Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock | Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled |
| THREE TRAY MODULE (OPTIONAL) | | | |
| Capacity ⁵ | Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets | | |
| Sizes | Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm | | |
| Weights One-sided: Two-sided: | 16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm | | |
| Types | Bond Plain Paper Cardstock Custom Hole Punched | Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock | Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled |
| ENVELOPE TRAY – REPLACES TRAY 1 (OPTIONAL) | | | |
| Capacity ⁵ | Up to 60 envelopes | | |
| Sizes | #10 commercial, Monarch, DL, C5 Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 mm to 162 x 241 mm | | |
| Weights | 20 lb. bond to 25 lb. bond/75 to 90 gsm | | |
| TOTAL CAPACITY | | | |
| Base Unit Capacity ⁵ | 620 sheets | | |
| Single Tray Module Capacity ⁵ | 1,140 sheets | | |
| Single Tray Module with Stand Capacity ⁴ | 1,140 sheets | | |
| Three Tray Module Capacity ⁵ | 2,180 sheets | | |
| FINISHING | | | |
| OUTPUT TRAYS | | | |
| Center Output Catch Trays | 500 sheets; tray offsets | | |
| INTEGRATED OFFICE FINISHER BOTH TYPES A AND GAR (OPTIONAL) | | | |
| Stacking Tray | 500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3 | | |
| Sizes | 3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 mm | | |
| Weights | 16 lb. bond to 80 lb. cover/60 to 220 gsm (Type GAR up to 256 gsm) | | |
| Stapling | Single Auto stapling: 50 sheets maximum: Letter/A4/B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4-size sheets (less than 90 gsm or (2) 220 gsm covers) (Type GAR supports dual stapling) | | |

Xerox® VersaLink® C7000 Color Printer

| DEVICE MANAGEMENT | |
|---|---|
| Network Protocols | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled |
| Administrative Protocols | DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS |
| REMOTE CONTROL PANEL | |
| | <ul style="list-style-type: none"> Enables faster, more convenient technical support and user training IT administrators and other authorized users can control the device remotely from a web page on any device Remote user experience is identical to performing tasks directly at the device |
| XEROX® CENTREWARE® WEB | |
| | <ul style="list-style-type: none"> A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management |
| XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE | |
| Device Status | <ul style="list-style-type: none"> Tray Status/Contents Consumables Status Billing/Usage Quick Links Online Support |
| Print Queue Viewing | Job print queue management — view and delete |
| Job Submission | Print-ready files (PS, PCL, PDF, XPS, JPEG) |
| Device Administration | Allows simple, remote installation setting of configuration options and management of the device |
| Browsers | Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™ |
| REMOTE SERVICES | |
| Xerox® Automatic Meter Reading (AMR) | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. |
| Xerox® Automatic Supplies Replenishment (ASR) | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory. |
| WHAT'S IN THE BOX | |
| | <ul style="list-style-type: none"> VersaLink® C7000 Color Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 3,300 print capacity⁶, Black: 5,300 print capacity⁶ Imaging Drum – One of each (Cyan, Magenta, Yellow, Black): 82,200 print capacity⁶ Quick Use Guide Quick Install Guide Software and Documentation CD (with Drivers, User Manual, System Admin. Guide and Warranty Statement) Power Cord |

Xerox® VersaLink® C7000 Color Printer

| SUPPLIES AND ACCESSORIES | QUANTITY | PART NUMBER |
|--|--|--|
| SUPPLIES | | |
| Standard Capacity Print Cartridges | Cyan: 3,300 standard pages ⁶ Magenta: 3,300 standard pages ⁶ Yellow: 3,300 standard pages ⁶ Black: 5,300 standard pages ⁶ | 106R03764 106R03763 106R03762 106R03761 |
| High Capacity Print Cartridges | Cyan: 10,100 standard pages ⁶ Magenta: 10,100 standard pages ⁶ Yellow: 10,100 standard pages ⁶ Black: 10,700 standard pages ⁶ | 106R03760 106R03759 106R03758 106R03757 |
| Worldwide Metered Print Cartridge | Cyan: 10,100 standard pages ⁷ Magenta: 10,100 standard pages ⁷ Yellow: 10,100 standard pages ⁷ Black: 10,700 standard pages ⁷ | 106R03756 106R03755 106R03754 106R03753 |
| CMYK Drum Cartridge | 82,200 standard pages ⁸ | 113R00782 |
| Waste Toner Bottle | 21,200 | 115R00129 |
| Fuser | 120V Fuser 220V Fuser | 115R00137 115R00138 |
| Staple Refills for Finishers (3 refills per container) | 15,000 staples (5,000 each refill) | 008R12941 |
| Staple Cartridge for Finishers (1 cartridge per container) | 5,000 staples (5,000 each cartridge) | 008R12964 |
| ACCESSORIES/OPTIONS | | |
| Single Tray Module (does not include stand) | | 097S04910 |
| Single Tray with Stand Module | | 097S04907 |
| Three Tray Module | | 097S04908 |
| Envelope Tray (This replaces Tray 1) | | 497K17720 |
| Integrated Office Finisher (Type A) | | 097S04911 |
| Integrated Office Finisher (Type GAR) | | 097S04847 |
| HDD (320 GB hard drive) (Optional) | | 497K17740 |
| Wireless Network Adapter Kit | | 497K16750 |
| Internal Card Reader/RFID Kit | | 497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere) |

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁷ Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in./A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.

⁸ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program.

For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.