

Xerox® VersaLink® C400 Colour Printer

VersaLink C400 Colour Printers are built on Xerox® ConnectKey® Technology.
For more information, go to www.ConnectKey.com.



SYSTEM SPECIFICATIONS	VERSALINK C400/DN
One-sided Speed¹ A4 / 210 x 297 mm 216 x 356 mm	Up to 35 ppm colour and black-and-white Up to 30 ppm colour and black-and-white
Two-sided Speed¹ A4 / 210 x 297 mm 216 x 356 mm	Up to 23 ppm colour and black-and-white Up to 21 ppm colour and black-and-white
Monthly Duty Cycle²	Up to 85,000 pages / month
Recommended Average Monthly Print Volume³	Up to 8,500 pages
Processor	1.05 GHz Dual-Core
Memory	2 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian
DEVICE SPECIFICATIONS	
ELECTRICAL REQUIREMENTS	
Europe and Other Geographies	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3Hz, 6 A

Xerox® VersaLink® C400 Colour Printer

POWER CONSUMPTION				
Continuous Printing⁴	705 watts or less			
Ready / Standby Mode⁴	76 watts or less			
Energy Saver / Sleep Mode⁴	4 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	0° C to 35° C			
Required Temperature Range (Operating)	10° C to 32° C			
Required Relative Humidity	10% to 85%			
Sound Power Levels Operating Standby	6.88 B(A) or less 5.0 B(A) or less			
Sound Pressure Levels Operating Standby	53.1 dB(A) or less 29.2 dB(A) or less			
Boot Time (from Off to UI Ready)	As fast as 60 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 6 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink C400/N and DN	491 mm	488 mm	399 mm	26 kg
550-sheet Paper Tray	427 mm	485 mm	138 mm	3.9 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink C400/N and DN	627 mm	638 mm	526 mm	30.45 kg
550-sheet Paper Tray	590 mm	544 mm	241 mm	5.3 kg
SYSTEM CERTIFICATION/REGULATORY COMPLIANCE				
To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .				
PRINT				
First-print-out Time	As fast as 13 seconds Colour / 12 seconds black-and-white			
Print Resolution	Up to 600 x 600 x 8 dpi (enhanced)			
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™			
Maximum Print Area	4 mm from edge of paper			

Xerox® VersaLink® C400 Colour Printer

<p>Print Features</p>	<p>Application Defaults Banner Pages Enable / Disable Bi-directional Real-time Status Booklet Layout Colour Adjustments (lightness, contrast, saturation, colour balance) Colour Correction Draft Mode Fit to new paper size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable / Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default – DN configuration) Watermark (predefined and custom) Earth Smart Driver Settings</p>
<p>Print from USB</p>	<p>Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</p>
<p>Operating Systems</p>	<p>Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP®</p> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.</p>
<p>Fonts</p>	<p>PostScript fonts: 136 PCL fonts: 83</p>
<p>Xerox® Global Print Driver®</p>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<p>Xerox® Pull Print Driver</p>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>
<p>MOBILE SOLUTIONS AND MOBILE DEVICE APPS</p>	
<p>Apple® AirPrint®</p>	<p>Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.</p>
<p>Google Cloud Print™</p>	<p>Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.</p>

Xerox® VersaLink® C400 Colour Printer

Xerox® @PrintByXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Print Management and Mobility Suite, Xerox® Print Management and Mobility Service	Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.
SOFTWARE SOLUTIONS	
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled device.
SECURITY	
Security Features	<ul style="list-style-type: none"> Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external programme falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM) <p>*Requires HDD/Productivity Kit</p>
ACCOUNTING	
XEROX® STANDARD ACCOUNTING TOOL / NETWORK ACCOUNTING (STANDARD)	
Tracking	Print usage
Accounting	<p>Xerox® Standard Accounting Tool</p> <ul style="list-style-type: none"> Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General accounts <p>Network Accounting (Job Based Accounting)</p> <ul style="list-style-type: none"> Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 accounting records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.

ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)																
	<ul style="list-style-type: none"> Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account 															
PAPER HANDLING																
BYPASS TRAY																
Capacity⁵	150 sheets															
Sizes	Custom sizes: 76.2 x 127 mm to 216 x 356 mm															
Weights One-sided: Two-sided:	60 to 220 gsm 60 to 163 gsm															
Types	<table border="0" style="width: 100%;"> <tr> <td>Plain</td> <td>Pre-Printed</td> <td>Glossy Cardstock</td> </tr> <tr> <td>Lightweight Cardstock</td> <td>Letterhead</td> <td>Labels</td> </tr> <tr> <td>Cardstock</td> <td>Bond</td> <td>Envelopes</td> </tr> <tr> <td>Hole Punched</td> <td>Lightweight Glossy Cardstock</td> <td>Custom</td> </tr> <tr> <td>Recycled</td> <td></td> <td></td> </tr> </table>	Plain	Pre-Printed	Glossy Cardstock	Lightweight Cardstock	Letterhead	Labels	Cardstock	Bond	Envelopes	Hole Punched	Lightweight Glossy Cardstock	Custom	Recycled		
Plain	Pre-Printed	Glossy Cardstock														
Lightweight Cardstock	Letterhead	Labels														
Cardstock	Bond	Envelopes														
Hole Punched	Lightweight Glossy Cardstock	Custom														
Recycled																
TRAY 1																
Capacity⁵	550 sheets															
Sizes	Custom sizes: 148 x 210 mm to 216 x 356 mm															
Weights One-sided: Two-sided:	60 to 220 gsm 60 to 163 gsm															
Types	<table border="0" style="width: 100%;"> <tr> <td>Plain</td> <td>Recycled</td> <td>Lightweight Glossy Cardstock</td> </tr> <tr> <td>Lightweight Cardstock</td> <td>Pre-Printed</td> <td>Glossy Cardstock</td> </tr> <tr> <td>Cardstock</td> <td>Letterhead</td> <td>Custom</td> </tr> <tr> <td>Hole Punched</td> <td>Bond</td> <td></td> </tr> </table>	Plain	Recycled	Lightweight Glossy Cardstock	Lightweight Cardstock	Pre-Printed	Glossy Cardstock	Cardstock	Letterhead	Custom	Hole Punched	Bond				
Plain	Recycled	Lightweight Glossy Cardstock														
Lightweight Cardstock	Pre-Printed	Glossy Cardstock														
Cardstock	Letterhead	Custom														
Hole Punched	Bond															
OPTIONAL TRAY 2																
Capacity⁵	550 sheets															
Sizes	Custom Sizes: 148 x 210 mm to 216 x 356 mm															
Weights One-sided: Two-sided:	60 to 220 gsm 60 to 163 gsm															
Types	<table border="0" style="width: 100%;"> <tr> <td>Plain</td> <td>Recycled</td> <td>Lightweight Glossy Cardstock</td> </tr> <tr> <td>Lightweight Cardstock</td> <td>Pre-Printed</td> <td>Glossy Cardstock</td> </tr> <tr> <td>Cardstock</td> <td>Letterhead</td> <td>Custom</td> </tr> <tr> <td>Hole Punched</td> <td>Bond</td> <td></td> </tr> </table>	Plain	Recycled	Lightweight Glossy Cardstock	Lightweight Cardstock	Pre-Printed	Glossy Cardstock	Cardstock	Letterhead	Custom	Hole Punched	Bond				
Plain	Recycled	Lightweight Glossy Cardstock														
Lightweight Cardstock	Pre-Printed	Glossy Cardstock														
Cardstock	Letterhead	Custom														
Hole Punched	Bond															
TOTAL CAPACITY																
Standard Device Capacity⁵	700 sheets															
Total Device Capacity⁵	1,250 sheets															
PAPER OUTPUT																
Output Capacity⁵	250 sheets															
Automatic Two-sided Printing	VersaLink C400N: NA VersaLink C400DN: Standard															
DEVICE MANAGEMENT																
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint™ Most protocols not in use can be disabled															
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS															

Xerox® VersaLink® C400 Colour Printer

REMOTE CONTROL PANEL	
	<ul style="list-style-type: none"> • Enables faster, more convenient technical support and user training • IT administrators and other authorized users can control the device remotely from a web page on any device • Remote user experience is identical to performing tasks directly at the device
XEROX® CENTREWARE® WEB SOFTWARE	
	<ul style="list-style-type: none"> • A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE	
Device Status	<ul style="list-style-type: none"> • Tray status/contents • Consumables status • Billing/Usage • Quick Links • Online Support
Print Queue Viewing	Job print queue management—view and delete
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
REMOTE SERVICES	
Automated Meter Reading (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automated Supplies Replenishment (ASR)	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory.
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox®, allowing for problems to be solved faster with increased uptime.
WHAT'S IN THE BOX	
	VersaLink C400 Colour Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 2,000 print capacity ⁶ , Black: 3,000 print capacity ⁶ Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord

Xerox® VersaLink® C400 Colour Printer

SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Standard Capacity Print Cartridges	Cyan: 2,500 standard pages ⁶ Magenta: 2,500 standard pages ⁶ Yellow: 2,500 standard pages ⁶ Black: 2,500 standard pages ⁶	106R03502 106R03503 106R03501 106R03500
High Capacity Print Cartridges	Cyan: 4,800 standard pages ⁶ Magenta: 4,800 standard pages ⁶ Yellow: 4,800 standard pages ⁶ Black: 5,000 standard pages ⁶	106R03514 106R03515 106R03513 106R03512
Extra High Capacity Print Cartridges	Cyan: 8,000 standard pages ⁶ Magenta: 8,000 standard pages ⁶ Yellow: 8,000 standard pages ⁶ Black: 10,500 standard pages ⁶	106R03526 106R03527 106R03525 106R03524
ROUTINE MAINTENANCE ITEMS		
Imaging Unit (includes 4 imaging units)	Cyan: 60,000 standard pages ⁷ Magenta: 60,000 standard pages ⁷ Yellow: 60,000 standard pages ⁷ Black: 60,000 standard pages ⁷	108R01121
Waste Cartridge	30,000 pages ⁷	108R01124
ACCESSORIES		
550-sheet Paper Tray		097S04400
Productivity Kit with 320 GB HDD		097S04914
Stand		497K13660
Wireless Network Adapter		497K16750

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

For more information, visit us at www.xerox.com/Office

Configurations vary by geography.

©2019 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, ConnectKey® Global Print Driver®, Mobile Express Driver®, SuppliesAssistant® and VersaLink® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. 8/19 PN03335_T121 BR26778 VC45S-01ED

