

# Xerox® VersaLink® C7000 Colour Printer



The VersaLink C7000 Colour Printer is built on Xerox® ConnectKey® Technology. For more information, go to [www.ConnectKey.com](http://www.ConnectKey.com).

SYSTEM SPECIFICATIONS	VERSALINK C7000N	VERSALINK C7000DN
<b>One-Sided Speed<sup>1</sup></b> A4 / 210 x 297 mm A3 / 297 x 420 mm	Up to 35 ppm (pages per minute) long edge feed (LEF) Up to 19 ppm	
<b>Two-Sided Speed<sup>1</sup></b> A4 / 210 x 297 mm A3 / 297 x 420 mm	N/A	35 ppm (pages per minute) LEF Up to 13 ppm
<b>Monthly Duty Cycle<sup>2</sup></b>	Up to 153,000 pages / month	
<b>Recommended Average Monthly Print Volume<sup>3</sup></b>	Up to 10,000 pages	
<b>Hard Drive</b>	320 GB HDD (Optional)	
<b>Processor</b>	1.05 GHz Dual-Core	
<b>Memory</b>	2 GB	
<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
<b>Controller Features</b>	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support	
<b>User Interface Languages</b>	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian	
<b>DEVICE SPECIFICATIONS</b>		
<b>ELECTRICAL REQUIREMENTS</b>		
<b>Europe and Other Geographies</b>	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3% Hz, 8 A	

# Xerox® VersaLink® C7000 Colour Printer

<b>POWER CONSUMPTION</b>				
Printing <sup>4</sup>	1.6 kWh			
Standby Mode <sup>4</sup>	94 watts or less			
Sleep Mode <sup>4</sup>	1.4 watts or less			
<b>OPERATING ENVIRONMENT</b>				
Required Temperature Range (Storage)	0° to 35° C			
Required Temperature Range (Operating)	10 to 32° C			
Required Relative Humidity	10% to 85%			
Sound Power Levels	Printing: 6.75 B(A) or less Standby: 4.10 B(A) or less  <b>Full System (including finisher)</b> Printing: 7.52 B(A) Standby: 4.10 B(A)			
Sound Pressure Levels	Printing: 52.5 dB(A) Standby: 26.0 dB(A)  <b>Full System (including finisher)</b> Printing: 60.0 dB(A) Standby: 26.0 dB(A)			
Boot Time (from Off to UI Ready)	As fast as 98 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 12 seconds			
<b>DIMENSIONS AND WEIGHT (UNPACKAGED)</b>	<b>WIDTH</b>	<b>DEPTH</b>	<b>HEIGHT</b>	<b>WEIGHT</b>
Base Unit	590 mm	670.8 mm	637 mm	54.3 kg
Base Unit with Single Tray with Stand Module	615.7 mm	670.8 mm	1118.6 mm	77.6 kg
Base Unit with Three Tray Module	615.7 mm	670.8 mm	1118.6 mm	81.8 kg
Base Unit with Three Tray Module and Integrated Office Finisher	615.7 mm	670.8 mm	1118.6 mm	97.6 kg
<b>CERTIFICATIONS</b>				
To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .				
<b>PRINT</b>				
First-print-out Time	As fast as 7.6 seconds colour			
	As fast as 5.1 seconds black-and-white			
Print Resolution	Up to 1200 x 2400 dpi			
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™			
Maximum Print Area	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper			

# Xerox® VersaLink® C7000 Colour Printer

<p><b>Print Features</b></p>	<p>Application Defaults            Banner Pages Enable / Disable            Bi-directional Real-time Status            Booklet Layout            Colour Adjustments (lightness, contrast, saturation, colour balance)            Colour Correction            Draft Mode            Finishing (requires finishing)            Fit to New Paper Size            Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)            Job Monitoring (Client or Local User Interface)            N-up Page Layout (up to 16 pages per sheet)            Paper Selection by Attribute            Personal Print            Print Around Enable / Disable            Print from USB            Run Black            Sample Set            Saved Job            Scaling            Secure Print            Skip Blank Pages            Special Pages (exception page programming: covers, inserts, exceptions pages)            Store and Recall Driver Settings            Stored Jobs Deletion            Two-sided Printing (as default – DN configuration)            Watermark (predefined and custom)            Earth Smart Driver Settings</p>
<p><b>Print from USB</b></p>	<p>Allows walk-up printing from Type A USB port            Supports direct printing from computer via Type B USB port            Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</p>
<p><b>Operating Systems</b></p>	<p>Windows® 7, 8, 8.1, 10            Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016            macOS® 10.11, 10.12, 10.13            Citrix®            Redhat® Enterprise Linux®            Fedora Core            IBM® AIX®            HP-UX®            Oracle® Solaris            SUSE®            SAP®</p> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers &amp; Downloads page and specify your device at <a href="http://www.Support.Xerox.com">www.Support.Xerox.com</a>.</p>
<p><b>Fonts</b></p>	<p>PostScript fonts: 136            PCL fonts: 83</p>
<p><b>Xerox® Global Print Driver®</b></p>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<p><b>Xerox® Pull Print Driver</b></p>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>
<p><b>MOBILE SOLUTIONS AND MOBILE DEVICE APPS</b></p>	
<p><b>Apple® AirPrint®</b></p>	<p>Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.</p>
<p><b>Google Cloud Print™</b></p>	<p>Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.</p>

# Xerox® VersaLink® C7000 Colour Printer

<b>Mopria® Certified</b>	ConnectKey Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.
<b>Xerox® @printbyXerox App</b>	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
<b>Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)</b>	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
<b>Xerox® Workplace Suite and Xerox® Workplace Cloud</b>	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.
<b>SOFTWARE SOLUTIONS</b>	
<b>Xerox® ConnectKey Apps (Found at the Xerox App Gallery)</b>	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the device.
<b>SECURITY</b>	
<b>Security Features</b>	<ul style="list-style-type: none"> <li>Access Controls</li> <li>AES 256-bit Encryption</li> <li>Audit Log</li> <li>Certificate Path Validation</li> <li>Certificate Revocation List (CRL)/Status Protocol (OCSP)</li> <li>Detection of external program falsification (XCP Plug-in)</li> <li>Cisco® Identity Services Engine (ISE) Integration</li> <li>Domain Filtering</li> <li>FIPS 140-2</li> <li>Firmware Verification</li> <li>Immediate Disk Overwrite*</li> <li>IP Address Filtering</li> <li>IPsec</li> <li>Network Authentication</li> <li>Port Filtering</li> <li>Pre-installed Self-Signed Certificates</li> <li>Role Based Permissions</li> <li>Secure Print</li> <li>Security Certificate Management</li> <li>Smart Card Enablement (CAC/PIV/.NET)</li> <li>SNMPv3</li> <li>Status Protocol (OCSP)</li> <li>TLS/SSL</li> <li>Trusted Platform Module (TPM)</li> </ul> <p>*Requires HDD/Productivity Kit</p>

ACCOUNTING			
<b>XEROX® STANDARD ACCOUNTING / NETWORK ACCOUNTING (STANDARD)</b>			
<b>Tracking</b>	Print usage		
<b>Accounting</b>	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts Up to 500 General Accounts  Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs Up to 14,000 Accounting Records (transactions)		
<b>Features</b>	Administrator can manage the feature via the Embedded Web Server.		
<b>ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)</b>			
	<ul style="list-style-type: none"> <li>Enhanced network accounting with up-to-the-minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device print usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul>		
PAPER HANDLING			
<b>BYPASS TRAY</b>			
<b>Capacity<sup>5</sup></b>	100 sheets		
<b>Sizes</b>	Custom sizes: 88.9 x 98.4 mm to 297 x 431.8 mm		
<b>Weights</b> One-sided: Two-sided:	60 to 216 gsm 60 to 169 gsm		
<b>Media Types</b>	Bond Plain Paper Cardstock Custom Envelopes	Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Pre-Printed Recycled
<b>TRAY 1</b>			
<b>Capacity<sup>5</sup></b>	520 sheets		
<b>Sizes</b>	Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm		
<b>Weights</b> One-sided: Two-sided:	60 to 256 gsm 60 to 169 gsm		
<b>Media Types</b>	Bond Plain Paper Cardstock Custom Hole Punched	Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
<b>SINGLE TRAY MODULE (OPTIONAL)</b>			
<b>Capacity<sup>5</sup></b>	520 sheets		
<b>Sizes</b>	Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm		
<b>Weights</b> One-sided: Two-sided:	60 to 256 gsm 60 to 169 gsm		

# Xerox® VersaLink® C7000 Colour Printer

<b>Media Types</b>	Bond Plain Paper Cardstock Custom Hole Punched	Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
<b>SINGLE TRAY MODULE WITH STAND (OPTIONAL)</b>			
<b>Capacity<sup>5</sup></b>	520 sheets		
<b>Sizes</b>	Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm		
<b>Weights</b> One-sided: Two-sided:	60 to 256 gsm 60 to 169 gsm		
<b>Types</b>	Bond Plain Paper Cardstock Custom Hole Punched	Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
<b>THREE TRAY MODULE (OPTIONAL)</b>			
<b>Capacity<sup>5</sup></b>	Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets		
<b>Sizes</b>	Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm		
<b>Weights</b> One-sided: Two-sided:	60 to 256 gsm 60 to 169 gsm		
<b>Types</b>	Bond Plain Paper Cardstock Custom Hole Punched	Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
<b>ENVELOPE TRAY – REPLACES TRAY 1 (OPTIONAL)</b>			
<b>Capacity<sup>5</sup></b>	Up to 60 envelopes		
<b>Sizes</b>	#10 commercial, Monarch, DL, C5 Custom sizes: 98 x 148 mm to 162 x 241 mm		
<b>Weights</b>	75 to 90 gsm		
<b>TOTAL CAPACITY</b>			
<b>Base Unit Capacity<sup>5</sup></b>	620 sheets		
<b>Single Tray Module Capacity<sup>5</sup></b>	1,140 sheets		
<b>Single Tray Module with Stand Capacity<sup>4</sup></b>	1,140 sheets		
<b>Three Tray Module Capacity<sup>5</sup></b>	2,180 sheets		
<b>FINISHING</b>			
<b>OUTPUT TRAYS</b>			
<b>Center Output Catch Trays</b>	500 sheets; tray offsets		
<b>INTEGRATED OFFICE FINISHER (OPTIONAL)</b>			
<b>Stacking Tray</b>	80 gsm – 8.5 x 11 in. / A4 or 80 gsm – 11 x 17 in. / A3		
<b>Sizes</b>	89 x 98 mm to 297 x 432 mm		
<b>Weights</b>	60 to 220 gsm		

# Xerox® VersaLink® C7000 Colour Printer

<b>Stapling</b>	Single Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)
<b>DEVICE MANAGEMENT</b>	
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint® FTP Most protocols not in use can be disabled
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
<b>REMOTE CONTROL PANEL</b>	
	<ul style="list-style-type: none"> <li>• Enables faster, more convenient technical support and user training</li> <li>• IT administrators and other authorized users can control the device remotely from a web page on any device</li> <li>• Remote user experience is identical to performing tasks directly at the device</li> </ul>
<b>XEROX® CENTREWARE® WEB</b>	
	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>
<b>EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE</b>	
<b>Device Status</b>	<ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Billing/Usage</li> <li>• Quick Links</li> <li>• Online Support</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management—view and delete
<b>Job Submission</b>	Print-ready files (PS, PCL, PDF, XPS, JPEG)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
<b>REMOTE SERVICES</b>	
<b>Automated Meter Readings (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Automatic Supplies Replenishment (ASR)</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
<b>WHAT COMES IN THE BOX</b>	
	<ul style="list-style-type: none"> <li>• VersaLink C7000 Colour Printer</li> <li>• Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 3,300 print capacity<sup>6</sup>, Black: 5,300 print capacity<sup>6</sup></li> <li>• Imaging Drum – One of each (Cyan, Magenta, Yellow, Black): 82,200 print capacity<sup>6</sup></li> <li>• Quick Use Guide</li> <li>• Quick Install Guide</li> <li>• Software and Documentation CD (with Drivers, User Manual, System Admin. Guide and Warranty Statement)</li> <li>• Power Cord</li> </ul>

# Xerox® VersaLink® C7000 Colour Printer

SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
<b>SUPPLIES</b>		
Standard Capacity Print Cartridges	Cyan: 3,300 standard pages <sup>6</sup> Magenta: 3,300 standard pages <sup>6</sup> Yellow: 3,300 standard pages <sup>6</sup> Black: 5,300 standard pages <sup>6</sup>	106R03764 106R03763 106R03762 106R03761
High Capacity Print Cartridges	Cyan: 10,100 standard pages <sup>6</sup> Magenta: 10,100 standard pages <sup>6</sup> Yellow: 10,100 standard pages <sup>6</sup> Black: 10,700 standard pages <sup>6</sup>	106R03760 106R03759 106R03758 106R03757
CMYK Drum Cartridge	82,200 standard pages <sup>7</sup>	113R00782
Waste Toner Bottle	21,200	115R00129
Staple Refills for Finishers (3 refills per container)	15,000 staples (5,000 each refill)	008R12941
Staple Cartridge for Finishers (1 cartridge per container)	5,000 staples (5,000 each cartridge)	008R12964
<b>ACCESSORIES / OPTIONS</b>		
Single Tray Module (does not include stand)		097S04910
Single Tray with Stand Module		097S04907
Three Tray Module		097S04908
Envelope Tray (This replaces Tray 1)		497K17720
Integrated Office Finisher		097S04911
HDD (320 GB hard drive) (Optional)		497K17740
Wireless Network Adapter Kit		497K16750
Unicode Printing Kit		320500291

<sup>1</sup> Declared print speed in accordance with ISO/IEC 24734.

<sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

<sup>4</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

<sup>5</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

<sup>7</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

For more information, visit us at [www.xerox.com/Office](http://www.xerox.com/Office).

Configurations vary by geography.