

# Xerox® PrimeLink® C9065/C9070 Printer



Meet the Xerox® PrimeLink C9065/C9070. Engineered to make a great first impression, these intuitive printers come complete with spot-on colour fidelity, best-in-class media latitude and professional finishing capabilities.

SYSTEM SPECIFICATIONS	PRIMELINK C9065		PRIMELINK C9070	
	COLOUR	BLACK-AND-WHITE	COLOUR	BLACK-AND-WHITE
<b>SIMPLEX SPEEDS</b>				
<b>A4</b> 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 177 to 350 gsm uncoated 151 to 350 coated	Up to 65 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm	Up to 70 ppm Up to 70 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm	Up to 70 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm Up to 35 ppm	Up to 75 ppm Up to 75 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm
<b>A3</b> 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 177 to 350 gsm uncoated 151 to 350 coated	Up to 32 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm Up to 14 ppm	Up to 35 ppm Up to 35 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm	Up to 35 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm Up to 17 ppm	Up to 37 ppm Up to 37 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm
<b>SRA3</b> 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 177 to 350 gsm uncoated 151 to 350 coated	Up to 29 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 30 ppm Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm	Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 33 ppm Up to 33 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm
<b>AUTO DUPLEX SPEEDS</b>				
<b>A4</b> Example: 60 to 105 gsm uncoated	Up to 65 ipm 2-sided 32 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 75 ipm 2-sided 37 sheets per minute
<b>A3</b> Example: 60 to 105 gsm uncoated	Up to 33 ipm 2-sided 16 sheets per minute	Up to 35 ipm 2-sided 17 sheets per minute	Up to 35 ipm 2-sided 17 sheets per minute	Up to 37 ipm 2-sided 18 sheets per minute
<b>Monthly Duty Cycle</b>	Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis). <sup>1</sup>			
<b>Average Monthly Print Volume (AMPV)</b>	10,000 to 50,000 pages per month <sup>2</sup>			

# Xerox® PrimeLink® C9065/C9070 Printer

<b>Technology</b>	Xerox® EA-Eco toner with Ultra Low Melt Technology (2400 x 2400 dots per inch)
<b>Control Panel Languages</b>	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan
<b>ACCESSORIES</b>	
<b>Optional</b>	<p>Xerox® EX-c C9065/C9070 Print Server Powered by Fiery®</p> <p>Xerox® EX-i C9065/C9070 Print Server Powered by Fiery®</p> <p>Xerox® EX C9065/C9070 Print Server Powered by Fiery®</p> <p>Simple Catch Tray (Europe only)</p> <p>Offset Catch Tray</p> <p>High Capacity Feeder (A4)</p> <p>1-Tray Oversized High Capacity Feeder with Storage Cabinet</p> <p>2-Tray Oversized High Capacity Feeder</p> <p>Interface Decurler Module</p> <p>Xerox® Business Ready Finisher (requires a Vertical Transport Kit)</p> <p>Xerox® Business Ready Finisher Booklet Maker (requires a Vertical Transport Kit)</p> <p>Xerox® Production Ready Finisher (requires Interface Decurler Module)</p> <p>Xerox® Production Ready Booklet Maker Finisher (requires Interface Decurler Module)</p> <p>Xerox® Production Ready Finisher Plus (includes PFIM Partner Finishing Interface Module; requires Interface Decurler Module)</p> <p>XLS Extension Tray Kits</p> <p>Plockmatic Pro50/35™ Booklet Maker</p> <p>Xerox® C/Z Folder</p> <p>Xerox® Basic Punch</p> <p>OHCF Chute</p> <p>MSI Assembly Kit</p> <p>Swedish 4-Hole Punch</p> <p>Envelope Fuser Kit</p> <p>Simple Offset Catch Tray</p> <p>Banner Feed Extension Long</p> <p>USB HUB Kit</p> <p>GBC® AdvancedPunch™ Pro</p> <p>Xerox® Crease/Two-sided Trimmer</p> <p>Xerox® SquareFold® Trimmer Module</p> <p>Xerox® Inserter</p> <p>Convenience Stapler</p> <p>Foreign Device Interface Kit</p> <p>Mobility Plate</p> <p>PostScript Kit</p> <p>VOIP Fax (SW) Kit</p> <p>Fax Kits (1 or 3 Line; requires fax installation kit)</p> <p>Server Fax Kit</p> <p>Xerox® Workplace Suite, Xerox® Workplace Cloud</p> <p>For More information on Xerox® Apps and Solutions, visit <a href="http://www.xerox.com/AppGallery">www.xerox.com/AppGallery</a>.</p>
<b>ELECTRICAL REQUIREMENTS</b>	
<b>Europe</b>	Voltage: 220-240V Frequency: 50/60 Hz +/- 3%, 10 A
<b>Accessories</b> Europe:	Each module requires 220V, 10 A
<b>POWER CONSUMPTION</b>	
<b>Running (Average)</b>	PrimeLink C9065: 1,052 watts; PrimeLink C9070: 1,250 watts
<b>Sleep Mode (Average)</b>	3 watts (Default time to Sleep mode = 1 min.)
<b>Low Power Mode Recovery Time</b>	Less than 20 seconds

<b>OPERATING ENVIRONMENT</b>			
<b>Required Temperature Range</b>	10° to 28° C (Relative Humidity less than 62.5% when temp is 32° C or less)		
<b>Required Relative Humidity</b>	15% to 85% (no condensation)		
<b>Sound Power Levels</b>	Operating: 6.8 B(A); Standby: 3.6 B(A)		
<b>Sound Pressure Levels</b>	Operating: 56 dB(A); Standby: 18 dB(A)		
<b>Weight (approximate base unit only)</b>	273 kg		
<b>DIMENSIONS</b>	<b>WIDTH</b>	<b>DEPTH</b>	<b>HEIGHT</b>
<b>Base Unit w/ Offset Catch Tray</b>	1,574 mm	803.5 mm	1,391.5 mm
<b>Base Unit w/ Business Ready Finisher</b>	2,009 mm	803.5 mm	1,391.5 mm
<b>Base Unit w/ Business Ready Booklet Maker Finisher</b>	2,068 mm	803.5 mm	1,391.5 mm
<b>Base Unit w/ Business Ready Booklet Maker Finisher and C Fold / Z Fold Unit</b>	2,301 mm	803.5 mm	1,391.5 mm
<b>Base Unit w/ Production Ready Finisher</b>	2,120.63 mm	803.5 mm	1,391.5 mm
<b>Base Unit w/ Production Ready Booklet Maker Finisher</b>	2,399.43 mm	803.5 mm	1,391.5 mm
<b>Xerox® Crease/ Two-sided Trimmer</b>	760.5 mm	714.3 mm	991.5 mm
<b>Interface Decurler Module</b>	340 mm	724.3 mm	991.5 mm
<b>Xerox® SquareFold® Trimmer</b>	1,066.3 mm	724 mm	558.8 mm
<b>High Capacity Feeder</b>	389 mm	614 mm	377 mm
<b>One Tray Oversized High Capacity Feeder</b>	988 mm	762 mm	992 mm
<b>Two Tray Oversized High Capacity Feeder</b>	988 mm	762 mm	992 mm
<b>CERTIFICATIONS</b> To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .			
<b>Graphic Arts Credentials</b>	FOGRA certification* PANTONE® Matching System* PANTONE GOE* PANTONE PLUS* Adobe® PDF Print Engine* Adobe® PostScript® 3™ (certified) IDEAlliance Digital Press Certified to GRACoL® specifications *requires an additional Print Server option		

<b>PAPER HANDLING</b>	
<b>SINGLE-PASS DUPLEX AUTOMATIC DOCUMENT FEEDER (DADF) - NETWORK SCANNING</b>	
<b>Capacity<sup>3</sup></b>	250 sheets of plain paper – 75 gsm
<b>Speed</b>	Up to 270 ipm colour / 270 ipm black-and-white (2-sided, A4)
<b>Paper Sizes</b>	Custom sizes: A5 to A3
<b>Weights</b>	38 to 200 gsm
<b>TRAY 5 (BYPASS)</b>	
<b>Capacity<sup>3</sup></b>	Up to 250 sheets
<b>Sizes</b>	Custom sizes: 100 x 148 mm to 330.2 x 482.6 mm (A5 to SRA3); XLS sheet size: 330 x 660 mm
<b>Weights</b>	60 to 350 gsm (60 to 350 gsm uncoated; 106 to 350 gsm coated); XLS sheet: 60-220 gsm
<b>Envelope Capacity</b>	30 to 50 envelopes
<b>Envelope Sizes</b>	#10 Commercial, Monarch (including custom size), C4, C5 (Available as Tray 5 (Bypass). Paper Size Default within tools. Run flap open at the trail edge.) Custom sizes: 190 x 170 mm to 240 x 173 mm. Digital Laser envelopes recommended.
<b>Envelope Weights</b>	75 to 90 gsm
<b>TRAYS 1 TO 4</b>	
<b>Capacity<sup>3</sup></b>	Tray 1: 500 sheets Tray 2: 500 sheets Tray 3: 870 sheets Tray 4: 1,130 sheets
<b>Sizes</b>	Tray 1: A5 to SRA3 Tray 2: A5 to A3 Tray 3: B5, A4 Tray 4: B5, A4
<b>Weights</b>	Trays 1 and 2: 60 to 256 gsm (60 to 256 gsm uncoated; 106 to 220 gsm coated) Trays 3 and 4: 60 to 256 gsm (60 to 256 gsm uncoated; 106 to 220 gsm coated)
<b>OPTIONAL HIGH CAPACITY FEEDER (HCF)</b>	
<b>Capacity<sup>3</sup></b>	2,000 sheets
<b>Sizes</b>	184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4)
<b>Weights</b>	64 to 220 gsm (uncoated and coated)
<b>OPTIONAL OVERSIZED HIGH CAPACITY FEEDER (OHCF) – 1 OR 2 TRAY OPTIONS</b>	
<b>Capacity<sup>3</sup></b>	1 Tray OHCF: 2,000 sheets plus Storage Cabinet 2 Tray OHCF: 4,000 sheets
<b>Sizes</b>	1 Tray OHCF: 182 x 250 mm (B5) to 330x660 mm 2 Tray OHCF: 102 x 152 mm to 330x660 mm
<b>Weights</b>	60 to 350 gsm (uncoated and coated); XLS sheet: 60-220 gsm
<b>TOTAL CAPACITY</b>	
<b>Standard Capacity</b>	3,250 sheets (includes Tray 5 (Bypass) and Trays 1-4)
<b>Maximum Capacity</b>	7,250 sheets (includes Tray 5 (Bypass), Trays 1-4 and Two-tray Oversized High Capacity Feeder)
<b>Automatic Two-Sided</b>	256 gsm auto duplex 350 gsm manual duplex for all stocks from Tray 5 (Bypass) and optional Oversized High Capacity Feeder

<b>FINISHING</b>	
<b>OFFSET CATCH TRAY</b>	
<b>Capacity<sup>3</sup></b>	Up to 500-sheet stacking
<b>Simple Catch Tray (Europe Only)</b>	Up to 500-sheet stacking
<b>OPTIONAL BUSINESS READY FINISHER</b>	
<b>Capacity<sup>3</sup></b>	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple), A3 or 200 sets (single-position staple) A4
<b>Sizes</b>	A6 to SRA3 for stacking B5 to A3 for stapling A5 output to top tray; punch and offset
<b>Weights</b>	60 to 350gsm (coated and uncoated) Top Tray 60 to 256 gsm (coated and uncoated) Stacker Tray
<b>Stapling</b>	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported
<b>Hole Punch</b>	2-4 Hole Punch 4 Hole Swedish Punch (Optional)
<b>OPTIONAL BUSINESS READY BOOKLET MAKER FINISHER</b>	
<b>Capacity<sup>3</sup></b>	Offsetting Top Tray: 500 sheets of A4 unstapled Stacking Stapling Tray: 1,500 sheets of A4 / A3 / SRA3 unstapled or 200 stapled sets of A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of A3 / SRA3
<b>Sizes</b>	A6 to SRA3 for stacking B5 to A3 for stapling A5 output to top tray; punch and offset
<b>Weights</b>	60 to 350 gsm (coated and uncoated) Top Tray 60 to 256 gsm (coated and uncoated) Stacker Tray 60 to 256 gsm (coated and uncoated) Booklet Maker
<b>Stapling</b>	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported
<b>Hole Punch</b>	2-4 Hole Punch 4 Hole Swedish Punch (Optional)
<b>Booklet Maker</b>	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated), Bi-fold up to 5 sheets A3, A4, SRA3 supported
<b>OPTIONAL XEROX® C/Z FOLDER</b>	
<b>Types</b>	C Fold, Z Fold and Z Half Fold
<b>Capacity<sup>3</sup></b>	40 sheets
<b>Sizes</b>	C Fold and Z Fold: Letter – A4 SEF only Z Half Fold: A3 only
<b>Weights</b>	64 to 90 gsm
<b>Output Tray</b>	Envelope Tray: C Fold, Z Fold and Tri-fold Stacker Tray or Top Tray: Z Half Fold
<b>OPTIONAL PRODUCTION READY FINISHER (REQUIRES INTERFACE DECURLER MODULE)</b>	
<b>Capacity</b>	Top Tray: 500 sheets of 80 gsm, A4 Lower Tray: 3,000 sheets of 80 gsm, A4
<b>Sizes</b>	A6 to SRA3
<b>Weights</b>	60 to 350 gsm (coated and uncoated) Top Tray 60 to 256 gsm (coated and uncoated) Stacker Tray

<b>Multiposition Stapling</b>	Up to 100 sheets of 80 gsm
<b>Hole-punching</b>	2-4 Hole Punch 4 Hole Swedish Punch (Optional)
<b>Inserting Capacity</b> Capacity: Sizes: Weights:	250 sheets of 350 gsm A3, A4, B4, B5 64 to 350 gsm
<b>Decurling</b>	Included with Interface Decurler Module and Standard Finisher Bidirectional with Auto and Manual settings
<b>OPTIONAL PRODUCTION READY FINISHER PLUS (REQUIRES INTERFACE DECURLER MODULE)</b>	
	Provides same function as the Production Ready Finisher with a 500-sheet top tray and 2,000-sheet stacker tray. Used to connect third-party inline finishing options. Includes PFIM Partner Finishing Interface Module.
<b>OPTIONAL PRODUCTION READY FINISHER WITH BOOKLET MAKER (REQUIRES INTERFACE DECURLER MODULE)</b>	
<b>Capacity</b>	Top Tray: 500 sheets of 80 gsm, / A4 Lower Tray: 2,000 sheets of 80 gsm, / A4
<b>Sizes</b>	A6 to SRA3
<b>Weights</b>	60 to 350 gsm (coated and uncoated) Top Tray 60 to 256 gsm (coated and uncoated) Stacker Tray 60 to 256 gsm (coated and uncoated) Booklet Maker
<b>Multi-position Stapling</b>	Up to 100 sheets of 80 gsm
<b>Hole-punching</b>	2-4 Hole Punch (Optional) 4 Hole Swedish Punch (Optional)
<b>Inserting Capacity</b> Capacity: Sizes: Weights:	250 sheets of 350 gsm A3, A4, B4, B5 64 to 350 gsm
<b>Decurling</b>	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings
<b>Booklet Making Capacity</b>	Saddle-stitch 2 to 30 sheets of 79 gsm (uncoated) or 2 to 25 sheets (coated); Bi-fold up to 5 sheets A4, B4, A3, SRA3
<b>OPTIONAL XEROX® CREASE AND TWO-SIDED TRIMMER</b>	
<b>Trim Sheet Sizes</b>	194 mm x 210 mm to 330.2 mm x 488 mm
<b>Trim Booklet Sizes</b>	182 mm x 257 mm to 330.2 mm x 488 mm
<b>Crease Weights</b>	106-350 gsm coated
<b>Weights</b>	60-350 gsm (uncoated) and 106-350 gsm (coated)
<b>OPTIONAL GBC® ADVANCEDPUNCH PRO</b>	
<b>Punch Configuration Sizes</b>	148 x 210 mm (A5) LEF to 330 x 488 mm (SRA3) SEF
<b>Weights</b>	75 to 300 gsm (uncoated); 106 to 300 gsm (coated)
<b>Dies</b>	Wide selection of slide-in / slide-out GBC punch die sets available
<b>OPTIONAL XEROX® SQUAREFOLD® TRIMMER MODULE</b>	
<b>Capacity</b>	5 to 20-sheet booklets (up to 80 imaged sides) at 90 gsm 5 to 25-sheet booklets (up to 100 imaged sides) at 80 gsm
<b>Sizes</b>	Custom sizes: A4 to SRA3
<b>Weights</b>	64 to 350 gsm

# Xerox® PrimeLink® C9065/C9070 Printer

<b>OPTIONAL CONVENIENCE STAPLER</b>	
<b>Capacity</b>	50 sheets (90 gsm media)
<b>PRINT</b>	
<b>Print Resolution</b>	Up to 2400 x 2400 dpi
<b>Line Screens</b>	600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on print server / controller selected)
<b>Registration</b>	<ul style="list-style-type: none"> <li>• Advanced registration technology for tighter control</li> <li>• Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (Available on all configurations as a Maintenance Tool: Alignment Adjustment)</li> </ul> +/-1.2 mm front to back registration Internal Trays
<b>First-Print-Out Time</b>	PS- A4 LEF Simplex Colour 10.4 seconds / Black-and-white 8.5 seconds
<b>Print Features</b>	<ul style="list-style-type: none"> <li>• Print, copy, fax and scan, including scan to PC, USB or email, and mobile printing</li> <li>• Benchmark image quality with 2400 x 2400 dpi resolution and EA low melt EA-Eco toner for a smooth finish</li> <li>• Makes mobile printing simpler and more convenient</li> <li>• Expansive media range lets you print everything from postcards to posters, both coated and uncoated stock, up to 350 gsm</li> <li>• Xerox Extensible Interface Platform® (EIP 3.7.3) allows you to connect to third-party software solutions that you can access from the touch-screen of the device or on your own mobile device.</li> <li>• Your choice of servers to best fit your environment:               <ul style="list-style-type: none"> <li>– Xerox® Integrated Colour Server for the Xerox® PrimeLink C9065/C9070 Printer</li> <li>– Xerox® EX-c PrimeLink C9065/C9070 Print Server Powered by Fiery®</li> <li>– Xerox® EX-i PrimeLink C9065/C9070 Print Server Powered by Fiery</li> <li>– Xerox® EX PrimeLink C9065/C9070 Print Server Powered by Fiery</li> </ul> </li> </ul> Inline finishing options offer a professional polish with banner printing, stapling, hole-punching, folding and booklet making for presentations, brochures, reports and newsletters. Be secure with integrated security features such as IP filtering, image overwrite, secure print, encrypted Scan to Email, authentication and IPv6 support.
<b>Print Drivers</b>	Xerox® Smart Start Driver Installer, Xerox® Global Print Driver® (v3, v4)
<b>PRINT SOLUTIONS</b>	
<b>Mobile Printing</b> (optional)	Apple® AirPrint®, Google Cloud Print™ Ready, Mopria® Print Service Plug-in for Android, Wi-Fi Direct Printing, Xerox® @PrintByXerox App, See more at <a href="http://www.xerox.com/MobileSolutions">www.xerox.com/MobileSolutions</a> ; Xerox® Workplace Cloud/Suite Mobile Print Solution. Learn more at <a href="http://www.xerox.com/MobilePrintApp">www.xerox.com/MobilePrintApp</a> .
<b>Xerox Apps</b>	On Box Apps include Xerox® @printbyXerox App for mobile printing and Xerox App Gallery to download a multitude of Print Management Apps.
<b>COPY</b>	
<b>First-Copy-Out Time</b> From the Platen: From the DADF:	As fast as 7.8 seconds colour / 5.1 seconds black-and-white As fast as 9.6 seconds colour / 5.3 seconds black-and-white
<b>Warm Up Time</b>	90 seconds (from cold powered down to Ready Copy)
<b>Digital Imaging</b>	Auto colour Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) Includes subtypes lighter/darker Background suppression Auto and manual contrast Sharpness Colour balance, colour shift and saturation

<b>Reduce / Enlarge</b>	Variable zoom from 25 % to 400 % in 1 % increments Anamorphic zoom Six user-programmable percentages
<b>Special Features</b>	Auto paper select Auto reduction/enlargement to fit selected paper size Auto tray switching Automatic job recovery Auto colour selection Area designation Poster mode Annotation Single/Dual colour Booklet creation Multi-up – 2, 4 or 8 up Repeat image Negative image Mirror image Covers insertion (front only, front and back, back only, blank or printed) Build job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Job interrupt Book copying Sample job Mixed-size originals Sheet insert Stamping/Bates 2-in-1 X Y zoom Zoom range 25 to 400 % Margin shift Photo Mode Poster Mode Preset Reduce / Enlarge Programme ahead Covers Erase, Image Repeat, Image Rotate Interrupt
<b>SCAN</b>	
<b>Concurrency</b>	Scan while printing or while it is transferring scan to network or fax jobs
<b>Scan Features</b>	Mixed size originals Edge erase Reduction/enlargement Fit to size Scan build job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto background and shadow suppression Job flow sheets Scan to USB Preview scan job
<b>INPUT SPEED</b>	Up to 270 images per minute Duplex
<b>Resolution</b>	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
<b>Maximum Scan Area</b>	Originals up to A3
<b>Network Print Services</b>	Port 9100 RFC 1179 (LPR) Print to Mailbox and Release



Xerox® PrimeLink® C9065/C9070 Printer

<b>File Formats</b>	PDF Image Only PDF Searchable PDF (Linearized) PDF (A-1 Level A) TIFF V6 JFIF XPS
<b>Document Management Fields (Metadata)</b>	One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard
<b>Scan Features</b>	Scan to Home Scan to Desktop WIA Scan to Desktop TWAIN Scan to Mailbox Scan to FTP Scan to sFTP (via EIP solution) Scan via SMB Scan via HTTP Scan via HTTPS Scan to USB Storage Device Scan to Fax Server Scan to Multiple Destinations Scan to Microsoft Network Folder
<b>Supported Scan Destinations (Standard)</b>	Scan to Email, Scan to Folder, to PC, to Mailbox (private and public), Scan to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview
<b>Scan to Email Features</b>	Colour scanning, Auto Colour, Greyscale, Black-and-white Direct document email from device Manual or directory Exchange / Notes / LDAP address searching Signing and encryption Email over SSL Preview scan job
<b>Authentication</b>	SMTP authentication, POP before SMTP, System credentials Single sign-on (LDAP, SMB, Kerberos authentication) Scanning Security-TLS
<b>FAX (OPTIONAL) – ONE OR THREE LINE FAX OPTIONS</b>	
<b>Maximum Scan Area</b>	210 mm x 297 mm (A3)
<b>Fax Send Features</b>	iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination
<b>Fax Print Features</b>	Print from USB Storage Device Media Print Unicode Printing
<b>Fax Features</b>	iFax Lan Fax IP Fax (optional) Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination

DEVICE MANAGEMENT	
<b>XEROX® CENTREWARE® INTERNET SERVICES – INTEGRATED WEB PAGES PROVIDED BY THE DEVICE</b>	
<b>Device Status</b>	Web server embedded in Network Controller: <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Alerts</li> </ul>
<b>Job Submission</b>	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Internet Explorer Safari Mozilla Firefox Opera Chrome
<b>Support</b>	Install print/scan drivers and online support available via web page
<b>Languages Supported</b>	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese
REMOTE SERVICES	
<b>Automated Meter Readings (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Automatic Supplies Replenishment (ASR)</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
SECURITY	
<b>Features</b>	Access Controls AES 256-bit Encryption Audit Log Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Programme Falsification (XCP Plug-in) Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite IP Address Filtering IPsec Network Authentication Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management SNMPv3 Status Protocol (OCSP) TLS/SSL (TLS 1.0, 1.1, 1.2)
PRINT SERVER	
<b>XEROX® INTEGRATED COLOUR SERVER</b>	
<b>Processor</b>	1.6 GHz Dual-core
<b>Memory</b>	4 GB system plus 1 GB page memory
<b>System Disk</b>	320 GB Hard Disk Drive
<b>Display</b>	264.2 mm colour touchscreen flat-panel
<b>Device Operating System</b>	Linux

# Xerox® PrimeLink® C9065/C9070 Printer

<b>PDLs Page Description Languages</b>	Adobe® PostScript® 3™ PDF PCL® 5c, 6 XML Paper Specification (XPS®) (optional)	
<b>Operating Systems</b>	Windows® XP Windows Server 2003 (32- and 64-bit) Windows Server 2008 (32- and 64-bit) Windows Server 2012 Windows Vista (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Mac OS® 10.7 and above	Solaris® 9, 10 HP-UX® 11 v2 IBM® AIX® 5 Red Hat® Fecora® Core 15-17 Red Hat Enterprise 4 and 5 openSUSE® 11 and 12 Ubuntu® Unix®
<b>Print Drivers Supported</b>	Please refer to <a href="http://www.xerox.com/support">www.xerox.com/support</a> for specifics. As new operating system versions are added, support is also added for the Xerox® PrimeLink C9065/C9070 Printer. Also note that there is more than one print driver based on the configuration purchased (e.g., digital front ends, Xerox® Global Print Driver) <ul style="list-style-type: none"> <li>Windows 7, 32-bit</li> <li>Windows 7, 64-bit</li> <li>Windows 8, 32-bit</li> <li>Windows 8, 64-bit</li> <li>Windows 8.1 Update 1, 32-bit</li> <li>Windows 8.1 Update 1, 64-bit</li> <li>Windows 10, 32-bit</li> <li>Windows 10, 64-bit</li> <li>Windows 10S, 32 bit &amp; 64-bit</li> <li>Windows Server 2008, 32-bit (SP2)</li> <li>Windows Server 2008, 64-bit (SP2)</li> <li>Windows Server 2008 R2, 64-bit (SP1)</li> <li>Windows Server 2012, 64-bit</li> <li>Windows Server 2012 R2, 64-bit</li> <li>Windows Server 2016, 64-bit</li> <li>Windows Server 2019, 64-bit</li> <li>Citrix® Xen App 7.15</li> <li>Citrix® Xen Desktop 7.15</li> <li>Citrix® Virtual Apps and Desktops 7</li> <li>Novell Open Enterprise Server 2018</li> <li>Cluster: Windows Server 2008 32- and 64-bit, 2008 R2, 64-bit; Windows Server 2012 64-bit;</li> <li>Windows 2012 R2 64-bit, Windows Server 2016 &amp; 2019, 64</li> <li>macOS High Sierra (10.13)</li> <li>macOS Mojave (10.14)</li> <li>macOS Catalina (10.15)</li> <li>Fedora Core 29 x32</li> <li>Fedora Core 29 x64</li> <li>Fedora Core 30 x32</li> <li>Fedora Core 30 x64</li> <li>Ubuntu 18.04 x32 &amp; x64</li> <li>Ubuntu 19.04 x64</li> <li>OpenSuse 15.0 x32 &amp; x64</li> <li>Solaris 11.4 x86</li> <li>Solaris SPARC 11.4</li> <li>Power PC AIX 7.2</li> <li>Itanium HP-UX 11i v3 Update 18</li> <li>Xerox® Global Print Driver® v3 &amp; v4</li> </ul>	

# Xerox® PrimeLink® C9065/C9070 Printer

<b>Features</b>	<p>Automatic two-sided            Bi-directional print drivers provide device and job status            Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print)            Secure print            Delay print            Embedded web server for remote control/monitor/setup            Enhanced gloss            Sample set            Booklet creation            Cover selection            Paper selection by attribute            N-up            Watermarks            Banner sheets            Banner printing            Fit to new paper size            Output tray selection            Print calibration (with EFI)            Print from USB (No Print Driver required)</p>
<b>Connectivity</b>	Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec)
<b>ADDITIONAL PRINT SERVER OPTIONS</b>	
<b>XEROX® EX-C C9065/C9070 PRINT SERVER POWERED BY FIERY®</b>	
<b>Processor</b>	AMD® GX-424CC processor 2.4 GHz
<b>Memory</b>	2 GB RAM
<b>Hard Drive</b>	500 GB
<b>Server Operating System</b>	Linux®
<b>Print Languages (PDL)</b>	Adobe PostScript® Level 1,2,3, Adobe PDF, EPS, PCL® 6C, TIFF, JPG, and MicroSoft® native formats via Fiery® Hot Folders
<b>Features</b>	<p>Easy-to-use colour adjustment tools that deliver outstanding colour quality from all applications and file formats.</p> <ul style="list-style-type: none"> <li>• Print logo and corporate colours correctly (including PANTONE colours)</li> <li>• Print high-quality photos and images</li> <li>• Use Fiery VUE, the “visual print driver,” to create and print professional booklets quickly, easily and cost effectively in-house</li> <li>• Easily print files with mixed paper sizes and types</li> <li>• Fully integrated with Xerox® ConnectKey® Apps</li> <li>• Paper Catalogue</li> <li>• Command WorkStation</li> <li>• Fiery Freeform</li> <li>• Fiery Remote Scan</li> </ul>
<b>Connectivity</b>	Direct Connection (Single IP) & Optional Network Switch (Dual IP): TCP/IP, AppleTalk, SNMP, IPv4, IPv6, IPP, FTP, SMB, WSD, Bonjour, Port 9100
<b>Additional Options</b>	<ul style="list-style-type: none"> <li>• Options Bundle               <ul style="list-style-type: none"> <li>– Fiery Spot-On™ with PANTONE approved libraries</li> <li>– Fiery Hot Folders</li> <li>– Fiery Virtual Printers</li> <li>– Auto Trapping</li> </ul> </li> <li>• Colour Profiler Suite (with ES2000)</li> <li>• Network Hub Kit</li> <li>• Spot On</li> <li>• Hot Folders/ Virtual Printers</li> </ul>
<b>XEROX® EX-I C9065/C9070 PRINT SERVER POWERED BY FIERY®</b>	
<b>Processor</b>	Intel 3-6100 (3.7 GHz) Processor (Performance optimised by proprietary combination of EFI Technology, VX600 ASIC and software)
<b>Memory</b>	4 GB

## Xerox® PrimeLink® C9065/C9070 Printer

<b>Hard Drive</b>	500 GB
<b>Server Operating System</b>	Linux®
<b>Print Languages (PDL)</b>	Adobe PostScript® Level 1,2,3, Adobe PDF, EPS, PCL® 6C, TIFF, JPG, and MicroSoft® native formats via Fiery® Hot Folders
<b>Features</b>	<ul style="list-style-type: none"> <li>• Productivity starts with a fast RIP. The Integrated Fiery Colour Server enables you to print large and/or complex Microsoft® Office® documents, PowerPoint® files and colour-critical PDFs accurately and quickly.</li> <li>• Fully integrated with Xerox® ConnectKey® Apps.</li> <li>• Simplify and streamline your workflow. Automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers.</li> <li>• Take advantage of commonly used Fiery presets to save time when submitting jobs. With Fiery server technology, even novice users can perform complex jobs using the pre-set drivers configured for the task.</li> <li>• Get the colour right. Produce precise, exact colour from all applications, platforms and formats with Fiery colour management tools.</li> <li>• Turn up the impact with variable information. Customise your output to a specific audience with varying text, photos and graphics with the Integrated Fiery Colour Server's basic variable data printing capabilities.</li> <li>• Print high-quality photos and images</li> <li>• Use Fiery VUE, the "visual print driver," to create and print professional booklets quickly, easily and cost effectively in-house</li> <li>• Easily print files with mixed paper sizes and types</li> <li>• Command WorkStation</li> <li>• Fiery JDF</li> <li>• Secure Erase</li> <li>• Paper Catalogue</li> <li>• Fiery Compose</li> <li>• Fiery Remote Scan</li> </ul>
<b>Connectivity</b>	Direct Connection (Single IP) & Optional Network Switch (Dual IP): TCP/IP, AppleTalk, SNMP, IPv4, IPv6, IPP, FTP, SMB, WSD, Bonjour, Port 9100
<b>Additional Options</b>	<ul style="list-style-type: none"> <li>• Productivity Package <ul style="list-style-type: none"> <li>– Fiery ImageViewer</li> <li>– Fiery Image Enhance Visual Editor</li> <li>– Control Bar Builder</li> <li>– Postflight Report</li> <li>– Configurable Auto Trapping</li> <li>– Paper Simulation</li> <li>– Graphic Arts Filters for Hot Folders</li> <li>– Rush Print, Schedule Print and Print/Process Next</li> <li>– Fiery JobFlow Base</li> </ul> </li> <li>• Fiery impose</li> <li>• Colour Profiler Suite (with ES2000)</li> <li>• Network Hub Kit</li> </ul>
	For more information, go to <a href="http://www.xerox.com">www.xerox.com</a>
<b>XEROX® EX C9065/C9070 PRINT SERVER POWERED BY FIERY®</b>	
<b>Processor</b>	Intel® Core™ i5-6500 Processor (3.2 up to 3.6 GHz with Turbo), Quad Core
<b>Memory</b>	8 GB
<b>Hard Drive</b>	1 TB
<b>Server Operating System</b>	Windows 10
<b>Print Languages (PDL)</b>	Adobe PostScript® Level 3, Adobe PDF, EPS, PCL® 6C, PCL 5, TIFF, JPG, MicroSoft® native formats via Fiery® Hot Folders and Adobe PDF Print Engine (APPE)
<b>Features</b>	<ul style="list-style-type: none"> <li>• Job-based Calibration Integration <ul style="list-style-type: none"> <li>– Fiery Spot-On finds the best match of PANTONE®, PANTONE Series, RGB, CMYK, L*a*b* and Spot Colours</li> <li>– Colour Modes for professional proofing and enhanced production colour requirements – Maximum print density</li> </ul> </li> <li>• Fully integrated with Xerox ConnectKey® Apps.</li> <li>• Fiery technology increases your profits by delivering high-impact documents with vibrant images and colour that exceed your customers' expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down production.</li> </ul>

# Xerox® PrimeLink® C9065/C9070 Printer

	<ul style="list-style-type: none"> <li>• The Fiery Command WorkStation increases your production and reduces errors and waste by centralising job management via its intuitive user interface. Simplify your labour-intensive document composition and imposition tasks even more by using Fiery SeeSequence Impose and Compose's intuitive interface.</li> <li>• Print high-quality photos and images</li> <li>• Use Fiery VUE, the "visual print driver," to create and print professional booklets quickly, easily and cost effectively in-house</li> <li>• Easily print files with mixed paper sizes and types</li> <li>• Paper Catalogue</li> <li>• Sequential Printing</li> <li>• Fiery JDF</li> <li>• Insert Tabs</li> </ul>		
<b>Connectivity</b>	Direct Connection (Single IP) & Optional Network Switch (Dual IP): TCP/IP, AppleTalk, SNMP, IPv4, IPv6, IPP, FTP, SMB, WSD, Bonjour, Port 9100		
<b>Additional Options</b>  For more information, go to <a href="http://www.xerox.com">www.xerox.com</a>	<ul style="list-style-type: none"> <li>• Fiery Graphic Arts Package, Premium Edition (optional) provides expert tools for preflighting and troubleshooting jobs</li> <li>• Fiery Colour Profiler Suite (optional) creates, verifies and edits colour profiles with a single profiling solution</li> <li>• Furniture Kit – Monitor, Keyboard, and Mouse</li> <li>• Colour Profiler Suite (with ES2000)</li> <li>• Removable HDD</li> <li>• Network Hub Kit</li> </ul>		
<b>SUPPLIES</b>	<b>YIELD</b>	<b>PART NUMBER</b>	
<b>Toner Cartridges (Metered)</b>	Black	30,000 pages <sup>4</sup>	006R01521
	Cyan	34,000 pages <sup>4</sup>	006R01524
	Magenta	32,000 pages <sup>4</sup>	006R01523
	Yellow	34,000 pages <sup>4</sup>	006R01522
<b>Toner Cartridges (Sold)</b>	Black	30,000 pages <sup>4</sup>	006R01734 (NASG,ESG) 006R01738 (DMO)
	Cyan	34,000 pages <sup>4</sup>	006R01737 (NASG, ESG) 006R01741 (DMO)
	Magenta	32,000 pages <sup>4</sup>	006R01736 (NASG, ESG) 006R01740 (DMO)
	Yellow	34,000 pages <sup>4</sup>	006R01735 (NASG, ESG) 006R01739 (DMO)
<b>Black Drum Cartridge</b>	1 Cartridge	190,000 pages <sup>4</sup>	013R00663
<b>Colour Drum Cartridge</b>	1 Cartridge per Colour	85,000 pages <sup>4</sup>	013R00664
<b>Charge Corotron</b>	For Black Drum	190,000 pages <sup>4</sup>	013R00650
<b>Fuser</b>	110V	200,000 pages <sup>4</sup>	008R13102
	220V	200,000 pages <sup>4</sup>	008R13065
<b>Waste Toner Container</b>	1 Cartridge	50,000 pages <sup>4</sup>	008R12990
<b>Feed Roll Kits</b>	1 Assembly	300,000 pages <sup>4</sup>	008R13169

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

<sup>4</sup> Approximate pages. Declared Yield based on 5 page job size, 30% colour and 70% black-and-white ratio, using A4 media. Yield will vary based on media size, image area coverage, job run length, media orientation and usage patterns.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme.

For more information, visit [www.xerox.com/About-Xerox/Recycling](http://www.xerox.com/About-Xerox/Recycling).

Learn more at [www.xerox.com/PrimeLink](http://www.xerox.com/PrimeLink)