

# Xerox® VersaLink® B7125/B7130/B7135

## Multifunction Printer



Xerox® VersaLink® B7100 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to [www.connectkey.com](http://www.connectkey.com).

System Specifications	VersaLink® B7125	VersaLink® B7130	VersaLink® B7135
<b>One-sided Speed<sup>1</sup></b> 8.5 x 11 in./A4/210 x 297 mm	Up to 25 ppm (pages per minute) long edge feed (LEF)	Up to 30 ppm LEF	Up to 35 ppm LEF
8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm	Up to 16 ppm Up to 14 ppm	Up to 20 ppm Up to 17 ppm	Up to 22 ppm Up to 19 ppm
<b>Two-sided Speed<sup>1</sup></b> 8.5 x 11 in./A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm	Up to 25 ppm LEF Up to 10 ppm Up to 9 ppm	Up to 30 ppm LEF Up to 12 ppm Up to 11 ppm	Up to 35 ppm LEF Up to 13 ppm Up to 12 ppm
<b>Monthly Duty Cycle<sup>2</sup></b>	Up to 107,000 pages/month <sup>2</sup>	Up to 129,000 pages/month <sup>2</sup>	Up to 153,000 pages/month <sup>2</sup>
<b>Recommended Average Monthly Print Volume<sup>3</sup></b>	Up to 13,000 pages	Up to 15,000 pages	Up to 17,000 pages
<b>Hard Drive</b>	320 GB HDD (Optional on Desktop model)		
<b>Processor</b>	1.05 GHz Dual-Core		
<b>Memory</b>	4 GB		
<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair		
<b>Controller Features</b>	Embedded Security and Integrity Control, TLS1.3 Support, NIST800-171r1 Compliance Print on Available media, Mopria, Remote Install Wizard - Secure Fax Remote Enable/Disable, Air Print		
<b>User Interface Languages</b>	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian, Arabic		

# Xerox® VersaLink® B7125/B7130/B7135 Multifunction Printer

Device Specifications				
Electrical Requirements				
North America	Voltage: 110-127 V -10%/+6% Frequency: 50/60 Hz +/-3%, 12A			
Europe and Other Geographies	Voltage: 220-240 V +/-10% Frequency: 50 Hz +/-3%, 8A			
Power Consumption				
Printing <sup>6</sup>	25 ppm = 0.39 kWh or less; 30 ppm = 0.48 kWh or less; 35 ppm = 0.57 kWh or less			
Standby Mode <sup>6</sup>	110V: 100 watts or less; For 220V: 94 watts or less			
Sleep Mode <sup>6</sup>	0.4 Watts or less			
Operating Environment				
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)			
Required Temperature Range (Operating)	50 to 90° F (10 to 32° C)			
Required Relative Humidity	10% to 85%			
Sound Power Levels	Printing: 6.85 B(A) or less • 25 ppm = 6.65 B(A); 30 ppm = 6.80 B(A); 35 ppm = 6.85 B(A) Standby: 4.10 B(A) or less • 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A); 35 ppm = 4.10 B(A) <b>Full System (including Finisher and HCF)</b> Printing: 25 ppm = 7.18 B(A); 30 ppm = 7.30 B(A); 35 ppm = 7.40 B(A) Standby: 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A); 35 ppm = 4.10 B(A)			
Boot Time (from Off to UI Ready)	As fast as 60 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 12 seconds			
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
Base Unit (Desktop Model)	23.23 in./590 mm	26.41 in./670.8 mm	30.18 in./766.5 mm	119.5 lbs/54.2 kg
Base Unit with Single Tray with Stand Module	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./1117.2 mm	170.0 lbs./77.1 kg
Base Unit with High Capacity Tandem Tray Module	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./1117.2 mm	188.7 lbs./85.6 kg
Base Unit with Three Tray Module and Office Finisher with Booklet Maker	44.69 in./1135.2 mm	26.71 in./678.6 mm	44.04 in./1117.2 mm	261.7 lbs./118.7 kg
Base Unit with Three Tray Module and Integrated Office Finisher	26.30 in./668 mm	26.41 in./670.8 mm	44.04 in./1117.2 mm	204.6 lbs./92.8 kg
Base Unit with Three Tray Module, Office Finisher, Booklet Maker, and High Capacity Feeder	57.1 in./1451.4 mm	26.7 in./678.6 mm	44.04 in./1117.2 mm	325.62 lbs./147.7 kg
Base Unit with High Capacity Tandem Tray Module and Integrated Office Finisher	26.30 in./668 mm	26.41 in./670.8 mm	44.04 in./1117.2 mm	213.2 lbs./96.7 kg
Base Unit with High Capacity Tandem Tray Module, Office Finisher, Booklet Maker, and High Capacity Feeder	57.1 in./1451.4 mm	26.7 in./678.6 mm	44.04 in./1117.2 mm	334.22 lbs./151.6 kg
Certifications				
To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .				

# Xerox® VersaLink® B7125/B7130/B7135 Multifunction Printer Configuration



**130-sheet<sup>5</sup> Single-Pass Duplex Automatic Document Feeder (DADF)** saves time by simultaneously scanning both sides of two-sided documents with up to 80 impressions per minute (ipm). High paper capacity drives productivity, especially for tasks that require large batches of scanned or copied documents.

**User interface is an intuitive, tablet-like, 7-inch** tiltable touch screen that allows you to complete tasks in just a few effortless taps and lets you personalize your experience. Gain access to 100+ productivity apps through the **Xerox App Gallery**. Try it out at [xerox.com/VersaLink7100UI](http://xerox.com/VersaLink7100UI).

**The standard 520-sheet<sup>5</sup> Tray 1** handles media sizes from 5.5 x 7.17 in to 11.69 x 17 in/139.7 x 182 mm to 297 x 431.8 mm.


**The 100-sheet Bypass Tray** handles media sizes from 3.5 x 3.87 in to 11.69 x 17 in/88.9 x 98.4 mm to 297 x 431.8 mm.




**Card Reader Bay** and embedded USB port.<sup>9</sup>

### MAXIMIZE PAPER CAPACITY WITH ONE OF THESE FEEDING OPTIONS<sup>5</sup>


**The Single Tray Module** (optional with desktop model) increases total paper capacity to 1,140 sheets (includes Bypass Tray).




**The Stand Module** offers total paper capacity of 1,140 sheets (includes Bypass Tray) and provides storage for toner cartridges and other supplies




**The Three Tray Module** (optional with desktop model) increases total paper capacity to 2,180 sheets (includes Bypass Tray).




**The Tandem Tray Module** allows for total paper capacity of up to 3,140 sheets (includes Bypass Tray).



**The Envelope Tray** can replace Tray 1 to provide feeding of up to 60 envelopes.



**The High-Capacity Feeder** holds 2,000 sheets of Letter/A4 paper, increasing the maximum paper capacity to 5,140 sheets.



### INCREASE VERSATILITY WITH FINISHING OPTIONS<sup>5</sup>



**The Office Finisher** provides advanced finishing functions, 500 sheet stacker, 3 position stapling and optional hole punch.



**The Office Finisher with Booklet Maker** simplifies booklet making, including score and saddle-stitch. Use it to create 64-page saddle-stitched booklets (2 to 16 sheets).



**The Work Surface and Convenience Stapler** staples up to 50 sheets and provides plenty of elbow room to sort documents.



**The Dual Off-set Catch Trays<sup>10</sup>** stack up to 250 sheets each.



**The Integrated Office Finisher** provides 500-sheet stacking and 50-sheet, dual position stapling.

<sup>5</sup>Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

<sup>9</sup>USB ports can be disabled.

<sup>10</sup>HDD and Dual Off-set Catch Trays are optional on Desktop model.

# Xerox® VersaLink® B7125/B7130/B7135 Multifunction Printer

Print	VersaLink® B7125	VersaLink® B7130	VersaLink® B7135
<b>First-Print-Out Time</b>	As fast as 6.2 seconds	As fast as 5.2 seconds	As fast as 4.8 seconds
<b>Print Resolution</b>	Up to 1200 x 1200 dpi		
<b>Page Description Languages</b>	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™ (Optional)		
<b>Maximum Print Area</b>	4 mm from Lead edge of paper, 2 mm from Side and Trail edges of paper		
<b>Print Features</b>	<ul style="list-style-type: none"> <li>Application Defaults</li> <li>Banner Pages Enable/Disable</li> <li>Bi-directional Real-time Status</li> <li>Booklet Layout</li> <li>Draft Mode</li> <li>Finishing (requires finishing)</li> <li>Fit to New Paper Size</li> <li>Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)</li> <li>Job Monitoring (Client or Local User Interface)</li> <li>LAN Fax (requires Fax Kit)</li> <li>N-up Page Layout (up to 16 pages per sheet)</li> <li>Paper Selection by Attribute</li> <li>Personal Print</li> <li>Print Around Enable/Disable</li> <li>Print from USB</li> <li>Sample Set</li> <li>Saved Job</li> <li>Scaling</li> <li>Secure Print</li> <li>Skip Blank Pages</li> <li>Special Pages (exception page programming: covers, inserts, exceptions pages)</li> <li>Store and Recall Driver Settings</li> <li>Stored Jobs Deletion</li> <li>Two-sided Printing (as default)</li> <li>Watermark (predefined and custom)</li> <li>Earth Smart Driver Settings</li> </ul>		
<b>Print from USB</b>	<ul style="list-style-type: none"> <li>Allows walk-up printing from Type A USB port</li> <li>Supports direct printing from computer via Type B USB port</li> <li>Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</li> </ul>		
<b>Operating Systems</b>	<ul style="list-style-type: none"> <li>Windows®, 7, 8, 8.1, 10, 11</li> <li>Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016</li> <li>Mac OS® version 10.12, 10.13, 10.14, 10.15, 11, 12</li> <li>Citrix®</li> <li>Redhat® Enterprise Linux®</li> <li>Fedora Core</li> <li>SUSE®</li> <li>SAP®</li> <li>IBM® AIX®</li> <li>HP-UX®</li> <li>Oracle® Solaris</li> </ul> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers &amp; Downloads page and specify your device at <a href="http://www.support.xerox.com">www.support.xerox.com</a>.</p>		
<b>Fonts</b>	<ul style="list-style-type: none"> <li>PostScript fonts: 136</li> <li>PCL fonts: 83</li> </ul>		
<b>Xerox® Global Print Driver®</b>	A truly universal print driver that lets IT administrators install, upgrade and manage non-Xerox and Xerox® Devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management		
<b>Xerox® Pull Print Driver</b>	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others		

# Xerox® VersaLink® B7125/B7130/B7135 Multifunction Printer

Copy	VersaLink® B7125	VersaLink® B7130	VersaLink® B7135
<b>Document Scanner</b>	130-sheet Single-pass Duplex Automatic Document Feeder (DADF)		
<b>Document Scanner Size</b>	Platen: Up to 11.7 x 17 in./297 x 431.8 mm DADF: Up to 11.7 x 17 in./297 x 431.8 mm		
<b>Simplex Copy Speed</b>	Up to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 mm)	Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)	Up to 35 cpm (copies per minute) 8.5 x 11 in. Up to 35 cpm A4 (210 x 297 mm)
<b>Duplex Copy Speed</b>	Up to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 mm)	Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)	Up to 35 cpm (copies per minute) 8.5 x 11 in. Up to 35 cpm A4 (210 x 297 mm)
<b>First-Copy-Out Time</b>	As fast as 5.8 seconds	As fast as 4.3 seconds	As fast as 4.3 seconds
<b>Sides (input: output)</b>	1:1, 1:2, 2:2 and 2:1		
<b>Quantity</b>	1 to 999		
<b>Resolution (max.)</b>	Up to 600 x 600 dpi		
<b>Reduction/Enlargement</b>	Variable zoom from 25% to 400% in 1% increments		
<b>Concurrency</b>	Concurrent scanning and printing		
<b>Copy Features</b>	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping)* Automatic Background Suppression Book Copying with Center Erase Booklet Copying* Collation Darkness Control Edge Erase Front Cover ID Card Copy Image Enhancement Image Shift Lighten/Darken N-up Reduce/Enlarge 25% to 400% Original Orientation Original Size Original Type Page Layout Sample Copy Saturation Sharpness *Requires HDD/Productivity Kit		
<b>Scan</b>			
<b>Capability</b>	Black-and-white and color scanning		
<b>Concurrency</b>	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs		
<b>Simplex Input Speed</b>	Black-and-white: Scan up to 80 ipm – 8.5 x 11 in./A4 (210 x 297 mm) Color: Scan up to 80 ipm – 8.5 x 11 in./A4 (210 x 297 mm)		
<b>Duplex Input Speed</b>	Black-and-white: Scan up to 80 ipm – 8.5 x 11 in./A4 (210 x 297 mm) Color: Scan up to 80 ipm – 8.5 x 11 in./A4 (210 x 297 mm)		
<b>Resolution</b>	Optical – 600 x 600 dpi		
<b>Bit Depth</b>	24-bit color/8-bit grayscale		
<b>Maximum Scan Area</b>	Platen: 11.7 x 17 in./297 x 431.8 mm Document Feeder: 11.7 x 17 in./297 x 431.8 mm		
<b>Network Filing Protocols</b>	FTP SMTP SMB sFTP		

# Xerox® VersaLink® B7125/B7130/B7135 Multifunction Printer

Scan	
<b>File Formats</b>	JPG TIFF (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearized PDF (set via embedded web server) and PDF/A
<b>Scan Driver Compatibility (Network Only)</b>	WIA TWAIN
<b>Supported Scan Destinations</b>	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)
Workflow Scanning (Optional Features)	
<b>Scanning Apps and Xerox App Gallery</b>	Scan to: DocuShare Go, Dropbox, Google Drive, Microsoft OneDrive, Microsoft 365, Box, Xerox® Workplace Mobile App (iOS/Android). See the full list of apps available in the Xerox App Gallery: <a href="http://xerox.com/AppGallery">xerox.com/AppGallery</a>
PSTN One-Line or Three-Line Fax <sup>4</sup> (Optional)	
<b>Fax Speed</b>	33.6 Kbps
<b>Resolution</b>	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
<b>Compression</b>	MH, MR, MMR, JBIG
<b>Fax Features</b>	Walk-up Fax, includes LAN Fax, Direct Fax, Server Fax Enablement, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts)
Fax Over IP (Optional)	
<b>Compliance</b>	T.38 compliant IP/SIP
<b>Resolution</b>	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
<b>Compression</b>	MH, MR, MMR, JBIG
<b>Fax Features</b>	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts)
Mobile and Cloud-ready	
<b>Mobile Connectivity</b>	Near Field Communication (NFC); <b>Optional:</b> Wi-Fi Direct, Wi-Fi (802.11 b/g/n/ac)
<b>Mobile Printing</b>	Mopria® Scan, Apple AirPrint™, Xerox® Print Service (Android), @PrintByXerox App; <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android)
<b>Mobile Scanning</b>	Mopria® Scan, Apple AirPrint™; <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android)
<b>Mobile Apps and Xerox App Gallery</b>	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate. Visit <a href="http://xerox.com/WorkplaceApps">xerox.com/WorkplaceApps</a> to find apps by industry or workflow. Software and services: Xerox® DocuShare® Content Management Platform ( <a href="http://xerox.com/ecm">xerox.com/ecm</a> ), XMPie® ( <a href="http://xerox.com/XMPie">xerox.com/XMPie</a> ), Xerox® Workplace Solutions ( <a href="http://xerox.com/WorkplaceSolutions">xerox.com/WorkplaceSolutions</a> )
<b>Xerox® Workplace Central Platform</b>	One-platform consistency for seamless productivity across computers, mobile devices, and printers. With the Workflow Central platform's ever-expanding suite of cloud-based workflows, you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable, and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases
<b>Xerox® Workplace Suite and Xerox® Workplace Cloud</b>	<b>Optional:</b> Xerox® Workplace Suite is a modular set of workflows designed to save the customer's time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and a cloud based-version (Workplace Cloud) of this solution

# Xerox® VersaLink® B7125/B7130/B7135 Multifunction Printer

Security	
<b>Security Features</b>	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec McAfee® - Embedded Control and Integrity Control Whitelisting NIST800-171r1 Compliance Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role-based Permissions Secure Email Secure Fax Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS 1.3/SSL Support *Requires HDD/Productivity Kit
Accounting	
Xerox® Standard Accounting/Network Accounting (Standard)	
<b>Tracking</b>	Copy, Print, Fax, Scan and Email usage
<b>Accounting</b>	Xerox® Standard Accounting Feature Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)
<b>Features</b>	Administrator can manage the feature via the Embedded Web Server
Accounting Options – Network Accounting (Allows central server to manage all accounting)	
	<ul style="list-style-type: none"> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and fax</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details, visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul>

# Xerox® VersaLink® B7125/B7130/B7135 Multifunction Printer

Paper Handling	
<b>Document Feeder</b>	
<b>Capacity<sup>5</sup></b>	Duplex Automatic Document Feeder (DADF): 130 sheets
<b>Sizes</b>	Custom sizes: 1.93 x 3.35 in. to 11.69 x 17 in./49 x 85 mm to 297 x 431.8 mm
<b>Weights</b>	11 to 34 lb. bond/38 to 128 gsm Single-pass DADF allows simplex weights
<b>Bypass Tray</b>	
<b>Capacity<sup>5</sup></b>	100 sheets
<b>Sizes</b>	Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in./88.9 x 98.4 mm to 297 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 216 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
<b>Types</b>	Bond Cardstock Custom Envelopes Glossy Cardstock Glossy Cardstock Reload Heavyweight Labels Hole Punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Plain Paper Pre-printed Recycled
<b>Tray 1</b>	
<b>Capacity<sup>5</sup></b>	520 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
<b>Types</b>	Bond Cardstock Custom Extra Heavyweight Labels Glossy Cardstock Glossy Cardstock Reload Heavyweight Cardstock Heavyweight Cardstock Reload Heavyweight Glossy Cardstock Heavyweight Glossy Cardstock Reload Heavyweight Labels Hole Punched Labels Letterhead Lightweight Cardstock Plain Paper Pre-printed Recycled



# Xerox® VersaLink® B7125/B7130/B7135 Multifunction Printer

Single Tray Module (Optional – Base Model Only)	
<b>Capacity<sup>5</sup></b>	520 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
<b>Types</b>	Bond Cardstock Custom Extra Heavyweight Labels Glossy Cardstock Glossy Cardstock Reload Heavyweight Cardstock Heavyweight Cardstock Reload Heavyweight Glossy Cardstock Heavyweight Glossy Cardstock Reload Heavyweight Labels Hole Punched Labels Letterhead Lightweight Cardstock Plain Paper Pre-printed Recycled
Single Tray Module with Stand (Optional)	
<b>Capacity<sup>5</sup></b>	520 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
<b>Types</b>	Bond Cardstock Custom Extra Heavyweight Labels Glossy Cardstock Glossy Cardstock Reload Heavyweight Cardstock Heavyweight Cardstock Reload Heavyweight Glossy Cardstock Heavyweight Glossy Cardstock Reload Heavyweight Labels Hole Punched Labels Letterhead Lightweight Cardstock Plain Paper Pre-printed Recycled

## Xerox® VersaLink® B7125/B7130/B7135 Multifunction Printer

Three Tray Module (Optional)	
<b>Capacity<sup>5</sup></b>	Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
<b>Types</b>	Bond Cardstock Custom Extra Heavyweight Labels Glossy Cardstock Glossy Cardstock Reload Heavyweight Cardstock Heavyweight Cardstock Reload Heavyweight Glossy Cardstock Heavyweight Glossy Cardstock Reload Heavyweight Labels Hole Punched Labels Letterhead Lightweight Cardstock Plain Paper Pre-printed Recycled
High Capacity Tandem Tray Module (Optional)	
<b>Capacity<sup>5</sup></b>	Tray 2: 520 sheets Tray 3: 870 sheets Tray 4: 1,130 sheets
<b>Sizes</b>	Tray 2: Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm Tray 3: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5 Tray 4: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
<b>Types</b>	Bond Cardstock Custom Extra Heavyweight Labels Glossy Cardstock Glossy Cardstock Reload Heavyweight Cardstock Heavyweight Cardstock Reload Heavyweight Glossy Cardstock Heavyweight Glossy Cardstock Reload Heavyweight Labels Hole Punched Labels Letterhead Lightweight Cardstock Plain Paper Pre-printed Recycled

# Xerox® VersaLink® B7125/B7130/B7135 Multifunction Printer

Envelope Tray – Replaces Tray 1 (Optional)	
<b>Capacity<sup>5</sup></b>	Up to 60 envelopes
<b>Sizes</b>	#10 commercial, Monarch, DL, C5 Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 mm to 162 x 241 mm
<b>Weights</b>	20 to 25 lb. bond/75 to 90 gsm
High Capacity Feeder (Optional)	
<b>Capacity<sup>5</sup></b>	2,000 sheets
<b>Sizes</b>	Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 216 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Total Capacity	
<b>Base Unit Capacity<sup>5</sup></b>	620 sheets
<b>Single Tray Module Capacity<sup>5</sup></b>	1,140 sheets
<b>Single Tray Module with Stand Capacity<sup>5</sup></b>	1,140 sheets
<b>Three Tray Module Capacity<sup>5</sup></b>	2,180 sheets
<b>High-Capacity Tandem Tray Capacity<sup>5</sup></b>	3,140 sheets
Finishing	
Output Trays (Optional on Desktop Model)	
<b>Dual Off-set Catch Trays<sup>5</sup></b>	250 sheets each; Lower tray offsets
Integrated Office Finisher (Optional)	
<b>Stacking Tray</b>	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3
<b>Sizes</b>	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 mm
<b>Weights</b>	16 lb. bond to 80 lb. cover/60 to 256 gsm
<b>Stapling</b>	Dual Auto stapling: 50 sheets maximum: Letter/A4/B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4-size sheets (less than 90 gsm or (2) 220 gsm covers)
Office Finisher (Optional)	
<b>Capacity<sup>5</sup></b>	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4) (Dual stapling is standard)
<b>Sizes</b>	5.8 x 5.8 in. to 11.7 x 17 in./148 x 148 mm to 297 x 432 mm
<b>Weights</b>	16 lb. bond to 80 lb. cover/60 to 256 gsm
<b>Multiposition Stapling</b>	50 sheets of 24 lb. bond/90 gsm
<b>Hole Punch (Optional)</b> North America: Europe:	2-3 Hole Punch 2-4 Hole Punch
Booklet Maker for Office Finisher (Score/Crease, Saddle-Stitch Staple) (Optional)	
<b>Capacity<sup>5</sup></b>	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)
<b>Sizes</b>	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Ledger – 11 x 17 in./A3 SEF
<b>Saddle-stitch Stapling</b>	2-15 sheets/8-60 page booklet 16 lb. bond to 80 lb. cover/64 to 220 gsm
<b>Score/Crease</b>	1-15 sheets/unstapled/52-105 gsm
Convenience Stapler (Optional – Includes Work Surface)	
<b>Capacity<sup>5</sup></b>	50-sheet stapling 5,000 staples Requires a separate outlet

# Xerox® VersaLink® B7125/B7130/B7135 Multifunction Printer

Device Management	
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ FTP Most protocols not in use can be disabled
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
Xerox® CentreWare® Web Software	
	<ul style="list-style-type: none"> <li>• A web-based server application for network administrators that permits web browser-based device management from any workstation, running Windows, UNIX, or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>
Embedded Web Server – Integrated Device Web Page	
<b>Device Status</b>	<ul style="list-style-type: none"> <li>• Tray Status/Contents</li> <li>• Consumables Status</li> <li>• Billing/Usage</li> <li>• Quick Links</li> <li>• Online Support</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management — view and delete
<b>Job Submission</b>	Print-ready files (PS (with optional PostScript option), PCL, PDF, JPEG)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Xerox® Device Manager</b>	<p>Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:</p> <ul style="list-style-type: none"> <li>• Device monitoring and troubleshooting</li> <li>• Remote configuration of SNMP v3</li> <li>• Extensive reporting and discovery of new devices</li> <li>• Usage collection, chargeback, and billing capabilities</li> <li>• Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install</li> </ul>
<b>Xerox® Workplace Cloud</b>	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server
<b>Browsers</b>	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
Remote Services	
<b>Automatic Meter Readings (AMR)</b>	Automates the process of collecting and submitting meter reads for the tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time
<b>Automatic Supplies Replenishment (ASR)</b>	Automatically orders supplies for output devices from Xerox based on actual usage, eliminating the need to manually manage supplies inventory

# Xerox® VersaLink® B7125/B7130/B7135 Multifunction Printer

Supplies	Description	Yield
<b>Sold Toner Cartridges</b>	Black	34,300 Pages <sup>7</sup>
<b>Metered Toner Cartridges</b>	Black	36,500 Pages <sup>7</sup>
<b>Drum Cartridge</b>	Black	80,000 Pages <sup>8</sup>
<b>Booklet Maker Cartridge (8 cartridges per carton)</b>	1 Cartridge Carton	16,000 staples (2,000 each cartridge)
<b>Staple Refills for Finishers (3 refills per carton)</b>	1 Refill Carton	15,000 staples (5,000 each refill)
<b>Staple Cartridge for Finishers (1 cartridge per carton)</b>	1 Cartridge	5,000 staples

<sup>1</sup> Declared print speed in accordance with ISO/IEC 24734.

<sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

<sup>4</sup> Requires analog phone line.

<sup>5</sup> Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

<sup>6</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

<sup>7</sup> Average standard pages. Declared yield in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.

<sup>8</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed.

<sup>9</sup> For more information, visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

<sup>9</sup> USB ports can be disabled.

<sup>10</sup> HDD and Dual Off-set Catch Trays are optional on Desktop model.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program.

For more information, visit [www.xerox.com/About-Xerox/Recycling](http://www.xerox.com/About-Xerox/Recycling).

For more information, visit us at [www.xerox.com/Office](http://www.xerox.com/Office).

Configurations vary by geography.